



JCSI Root CA Certification Practice Statement

Version 2.1

English Version

Cybertrust Japan Co., Ltd.

May 10, 2019

***Note**

This “JCSI Root CA Certification Practice Statement Version 2.1” basically describes the following matters. However, please note that the following is a reference translation, and the effective statement is the original statement in the Japanese language. Please kindly note that Cybertrust Japan Co., Ltd. does not guarantee the accuracy of this English translation in comparison to the original statement in the Japanese language, and will not be liable in any way for any inconsistency between this English translation and the original statement in the Japanese language.

- Copyright and distribution conditions of this “JCSI Root CA Certification Practice Statement”
This CPS is available under Attribution-NoDerivs (CC-BY-ND) 4.0 (or later version) of the Creative Commons license.

©2019 Cybertrust Japan Co., Ltd. Version 2.1
date: 10th May 2019.

This CPS can be copied and distributed in whole or in part for free of charge if the following conditions are satisfied.

- Display the copyright notice, Version, and revision date in the top of its pages of whole or part of the copies.
- Set forth that full text can be obtained at <https://www.cybertrust.co.jp/jcsi/repository.html> if only a part of this document is distributed.
- Specify the citation source appropriately when using part of this document as excerpts and citations in other documents.
- Cybertrust Japan shall not be liable for any dispute or damage related to copying and distribution of this CPS.
- In addition, Cybertrust Japan will prohibit alteration and modification in any case.

Inquiries about the copyright and distribution conditions of this CPS will be accepted at this CPS "1.5.2 Contact Point".

Revision History

Version	Date	Reason for Revision
1.0	June 30, 2014	▪ Launch of JCSI Root CA, Formulation of Initial Version
1.1	March 30, 2017	▪ Made changes pursuant to the Baseline Requirements
1.2	July 20, 2017	▪ Made changes pursuant to the Baseline Requirements
1.3	February 21, 2018	▪ Made changes pursuant to the Baseline Requirements v1.5.6
1.4	April 23, 2018	▪ Correction of errors
1.5	June 1, 2018	▪ Remove "(iv) Other Method of Confirmation" from Section "3.2.2.5 Authentication for an IP Address"
1.6	September 5, 2018	▪ Made changes pursuant to "the JCSI certificate issuing service" ▪ Changed Address in "1.5.2 Contact Point" with headquarter shift ▪ Made changes pursuant to the Baseline Requirements
2.0	December 25, 2018	▪ Made changes pursuant to the "JCSI certificate issuing service" ▪ Made changes pursuant to the certificate profile of public and active intermediate CA ▪ Made changes pursuant to the Baseline Requirements ▪ Changed Repository URL from cybertrust.ne.jp to cybertrust.co.jp ▪ Correction of errors
2.1	May 10, 2019	▪ Made changes pursuant to the Baseline Requirements v1.6.5 ▪ Correction of errors

Table of Contents

1. INTRODUCTION	1
1.1 OVERVIEW.....	1
1.2 DOCUMENT NAME AND IDENTIFICATION.....	2
1.3 PKI PARTICIPANTS.....	2
1.3.1 Certification Authority.....	2
1.3.2 Registration Authority.....	2
1.3.3 Issuing Authority.....	3
1.3.4 Subscribers.....	3
1.3.5 Relying Parties.....	3
1.3.6 Other Relevant Parties.....	3
1.4 CERTIFICATE USAGE	3
1.4.1 Types of Certificates.....	3
1.4.2 Appropriate Certificate Usage	4
1.4.3 Prohibited Certificate Usage.....	5
1.5 POLICY ADMINISTRATION	5
1.5.1 Organization to Control Documents.....	5
1.5.2 Contact Point.....	5
1.5.3 Party to Determine Suitability of CPS.....	5
1.5.4 Suitability Approval Procedures.....	5
1.6 DEFINITIONS AND ACRONYMS.....	5
2. PUBLICATION AND REPOSITORY RESPONSIBILITIES.....	6
2.1 ORGANIZATION TO OPERATE REPOSITORIES.....	6
2.2 INFORMATION TO BE PUBLISHED	6
2.3 TIMING AND FREQUENCY OF PUBLICATION	6
2.4 ACCESS CONTROL ON REPOSITORIES	6
3. IDENTIFICATION AND AUTHENTICATION	7
3.1 NAMING	7
3.1.1 Types of Names.....	7
3.1.2 Need for Names to be Meaningful	7
3.1.3 Requirements for Anonymity or Pseudonymity of Subscribers.....	7
3.1.4 Rules for Interpreting Various Name Forms	7
3.1.5 Uniqueness of Names	7
3.1.6 Recognition, Authentication, and Role of Trademarks.....	7
3.2 INITIAL IDENTITY VALIDATION	7
3.2.1 Method to Prove Possession of Private Key.....	7
3.2.2 Authentication of Organization and Domain Identity.....	8
3.2.3 Authentication of Individual Identity.....	12
3.2.4 Non-verified Subscriber Information.....	12
3.2.5 Verification of Application Supervisor.....	12
3.2.6 Interoperability Standards.....	12
3.3 IDENTIFICATION AND AUTHENTICATION FOR KEY (CERTIFICATE) RENEWAL REQUEST	12
3.3.1 Identification and Authentication upon Renewal for Routine Key (Certificate) Renewal.....	12
3.3.2 Identification and Authentication for Renewal of Key (Certificate) after Revocation	12
3.4 IDENTITY VALIDATION AND AUTHENTICATION UPON REVOCATION REQUEST	13
4. CERTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS	14
4.1 CERTIFICATE APPLICATION	14
4.1.1 Persons Who May Apply for Certificates.....	14
4.1.2 Enrolment Process and Responsibilities	14
4.2 CERTIFICATE APPLICATION PROCESSING	14
4.2.1 Identity Validation and Execution of Certification Operations	14
4.2.2 Approval or Rejection of Certificate Application.....	14
4.2.3 Time Required for Certificate Application Procedures.....	14
4.3 CERTIFICATE ISSUANCE.....	15
4.3.1 Certificate Issuance Procedures by Certification Authority.....	15

4.3.2	<i>Notification of Issuance of Certificate</i>	15
4.4	CERTIFICATE ACCEPTANCE	15
4.4.1	<i>Certificate Acceptance Verification Procedures</i>	15
4.4.2	<i>Publication of Certificate by Certification Authority</i>	15
4.4.3	<i>Notification of Issuance of Certificate by Certification Authority to Other Participants</i>	15
4.5	KEY PAIR AND CERTIFICATE USAGE	15
4.5.1	<i>Use of Private Key and Certificate by Subscriber</i>	15
4.5.2	<i>Use of Subscriber's Public Key and Certificate by Relying Party</i>	15
4.6	CERTIFICATE RENEWAL NOT INVOLVING KEY RENEWAL	15
4.6.1	<i>Requirements for Certificate Renewal Not Involving Key Renewal</i>	15
4.6.2	<i>Persons Who May Request Renewal</i>	15
4.6.3	<i>Renewal Request Procedures</i>	16
4.6.4	<i>Notification of Issuance of Renewed Certificate</i>	16
4.6.5	<i>Procedures for Accepting Renewed Certificate</i>	16
4.6.6	<i>Publication of Renewed Certificate</i>	16
4.6.7	<i>Notification of Issuance of Certificate by Certification Authority to Other Participants</i>	16
4.7	CERTIFICATE RE-KEY	16
4.7.1	<i>Requirements for Certificate Renewal Involving Rekey</i>	16
4.7.2	<i>Persons Who May Request Renewal</i>	16
4.7.3	<i>Rekey Application Procedures</i>	16
4.7.4	<i>Notification of Issuance of Rekeyed Certificate</i>	16
4.7.5	<i>Procedures for Accepting Rekeyed Certificate</i>	16
4.7.6	<i>Publication of Rekeyed Certificate</i>	16
4.7.7	<i>Notification of Issuance of Rekeyed Certificate to Other Participants</i>	16
4.8	MODIFICATION OF CERTIFICATE	17
4.8.1	<i>Requirements for Modification of Certificate</i>	17
4.8.2	<i>Persons Who May Request Modification of Certificate</i>	17
4.8.3	<i>Certificate Modification Procedures</i>	17
4.8.4	<i>Notification of Issuance of Modified Certificate</i>	17
4.8.5	<i>Procedures for Accepting Modified Certificate</i>	17
4.8.6	<i>Publication of Modified Certificate</i>	17
4.8.7	<i>Notification of Issuance of Modified Certificate to Other Participants</i>	17
4.9	CERTIFICATE REVOCATION AND SUSPENSION	17
4.9.1	<i>Circumstance for Revocation</i>	17
4.9.2	<i>Persons Eligible for Applying for Revocation</i>	20
4.9.3	<i>Revocation Application Procedures</i>	20
4.9.4	<i>Grace Period up to Revocation Application</i>	20
4.9.5	<i>Time Required for Certification Authority to Process Revocation</i>	20
4.9.6	<i>Revocation Confirmation Method by Relying Parties</i>	20
4.9.7	<i>CRL Issue Cycle</i>	20
4.9.8	<i>Maximum Delay Time up to CRL Publication</i>	21
4.9.9	<i>Online Confirmation of Revocation Information</i>	21
4.9.10	<i>Online Certificate Revocation/Status Checking</i>	21
4.9.11	<i>Means for Providing Other Forms of Revocation Advertisements</i>	21
4.9.12	<i>Special Requirements on Compromise of Key</i>	21
4.9.13	<i>Certificate Suspension Requirements</i>	21
4.9.14	<i>Persons Eligible for Applying for Suspension</i>	21
4.9.15	<i>Suspension Application Procedures</i>	22
4.9.16	<i>Term of Suspension</i>	22
4.10	CERTIFICATE STATUS SERVICES	22
4.10.1	<i>Operational Characteristics</i>	22
4.10.2	<i>Service Availability</i>	22
4.10.3	<i>Other Requirements</i>	22
4.11	END OF SUBSCRIPTION (REGISTRATION)	22
4.12	KEY ESCROW AND RECOVERY	22
4.12.1	<i>Key escrow and recovery policy and practices</i>	22
4.12.2	<i>Session key encapsulation and recovery policy and practices</i>	22
5.	MANAGEMENT, OPERATIONAL, AND PHYSICAL CONTROLS	23
5.1	PHYSICAL SECURITY CONSTRUCTION	23
5.1.1	<i>Site Location and Structure</i>	23
5.1.2	<i>Physical Access</i>	23
5.1.3	<i>Power and Air-conditioning</i>	23
5.1.4	<i>Water-exposures Control Measures</i>	23

5.1.5	Fire Control Measures.....	23
5.1.6	Anti-earthquake Measures.....	23
5.1.7	Medium Storage Site.....	23
5.1.8	Waste Disposal.....	23
5.1.9	Off-site Backup.....	24
5.2	PROCEDURAL CONTROLS	24
5.2.1	Trusted Roles and Personnel	24
5.2.2	Number of Personnel Required for Each Role.....	24
5.2.3	Personal Identification and Verification of Each Role.....	24
5.2.4	Roles Requiring Segregation of Duties.....	25
5.3	PERSONNEL SECURITY CONTROLS	25
5.3.1	Qualifications, Experience, Clearances.....	25
5.3.2	Background Checks and Clearance Procedures.....	25
5.3.3	Training Requirements and Procedures.....	25
5.3.4	Retraining Period and Procedures.....	25
5.3.5	Frequency and Sequence for Job Rotation	25
5.3.6	Sanction against Unauthorized Actions.....	25
5.3.7	Contract Requirements of Contract Employees.....	25
5.3.8	Documents Available to Certification Authority Staff.....	26
5.4	AUDIT LOGGING PROCEDURES.....	26
5.4.1	Types of Events to be Recorded.....	26
5.4.2	Audit Logging Frequency.....	26
5.4.3	Audit Log Archival Period.....	26
5.4.4	Audit Log Protection.....	26
5.4.5	Audit Log Backup Procedures.....	26
5.4.6	Audit Log Collection System.....	26
5.4.7	Notification to Parties	26
5.4.8	Vulnerability Assessment	27
5.5	RECORDS ARCHIVAL	27
5.5.1	Records to be Archived.....	27
5.5.2	Record Archival Period.....	27
5.5.3	Record Protection.....	27
5.5.4	Record Backup Procedures.....	27
5.5.5	Time-stamping.....	27
5.5.6	Record Collecting System.....	27
5.5.7	Record Acquisition and Verification Procedures.....	27
5.6	KEY CHANGE OVER OF CERTIFICATION AUTHORITY	28
5.7	COMPROMISE AND DISASTER RECOVERY.....	28
5.7.1	Compromise and Disaster Recovery Procedures.....	28
5.7.2	Procedures upon System Resource Failure	28
5.7.3	Procedures upon Compromise of Subscriber Private Key	29
5.7.4	Business Continuity upon Disasters	29
5.8	TERMINATION OF CERTIFICATION AUTHORITY OPERATIONS	29
6.	TECHNICAL SECURITY CONTROLS.....	30
6.1	KEY PAIR GENERATION AND INSTALLATION.....	30
6.1.1	Key Pair Generation.....	30
6.1.2	Delivery of Subscriber Private Key.....	30
6.1.3	Delivery of Subscriber Public Key to Certification Authority	30
6.1.4	Delivery of Certification Authority Public Key to Relying Parties	30
6.1.5	Key Length.....	30
6.1.6	Generation and Check of Public Key Parameter	31
6.1.7	Key Usage	31
6.2	PRIVATE KEY PROTECTION AND CRYPTOGRAPHIC MODULE ENGINEERING CONTROLS	31
6.2.1	Cryptographic Module Standards and Controls	31
6.2.2	Private Key Controls by Multiple Persons	31
6.2.3	Private Key Escrow.....	32
6.2.4	Private Key Backup.....	32
6.2.5	Private Key Archive.....	32
6.2.6	Private Key Transfer.....	32
6.2.7	Private Key Storage in Cryptographic Module	32
6.2.8	Private Key Activation	32
6.2.9	Private Key Deactivation	32
6.2.10	Private Key Destruction.....	32

6.2.11	<i>Cryptographic Module Assessment</i>	32
6.3	OTHER ASPECTS OF KEY PAIR MANAGEMENT	33
6.3.1	<i>Storage of Public Key</i>	33
6.3.2	<i>Certificate Operational Periods and Key Pair Usage Periods</i>	33
6.4	ACTIVATION DATA	33
6.4.1	<i>Creation and Setting of Activation Data</i>	33
6.4.2	<i>Activation Data Protection and Controls</i>	33
6.4.3	<i>Other Aspects of Activation Data</i>	33
6.5	COMPUTER SECURITY CONTROLS	33
6.5.1	<i>Technical Requirements of Computer Security</i>	33
6.5.2	<i>Computer Security Assessment</i>	34
6.6	LIFE CYCLE SECURITY CONTROLS	34
6.6.1	<i>System Development Controls</i>	34
6.6.2	<i>Security Management Controls</i>	34
6.6.3	<i>Life Cycle Security Controls</i>	34
6.7	NETWORK SECURITY CONTROLS	34
6.8	TIME-STAMPING	34
7.	CERTIFICATE, CRL AND OSCP PROFILES	35
7.1	CERTIFICATE PROFILE	35
7.1.1	<i>Version No.</i>	35
7.1.2	<i>Certificate Extensions</i>	35
7.1.3	<i>Algorithm Object Identifier</i>	35
7.1.4	<i>Name Format</i>	35
7.1.5	<i>Name Restrictions</i>	35
7.1.6	<i>Certificate Policy Object Identifier</i>	35
7.1.7	<i>Use of Policy Constraint Extensions</i>	35
7.1.8	<i>Construction and Meaning of Policy Modifier</i>	35
7.1.9	<i>Processing Method of Certificate Policy Extensions</i>	35
7.2	CRL PROFILE	36
7.2.1	<i>Version No.</i>	36
7.2.2	<i>CRL, CRL Entry Extensions</i>	36
7.3	OCSP PROFILE	36
7.3.1	<i>Version No.</i>	36
7.3.2	<i>OCSP Extensions</i>	36
8.	COMPLIANCE AUDIT AND OTHER ASSESSMENT	37
8.1	AUDIT FREQUENCY AND REQUIREMENTS	37
8.2	AUDITOR REQUIREMENTS	37
8.3	RELATION OF AUDITOR AND AUDITEE	37
8.4	SCOPE OF AUDIT	37
8.5	MEASURES AGAINST IDENTIFIED MATTERS	37
8.6	DISCLOSURE OF AUDIT RESULTS	37
8.7	SELF-AUDITS	37
9.	OTHER BUSINESS AND LEGAL MATTERS	38
9.1	FEES	38
9.2	FINANCIAL RESPONSIBILITY	38
9.3	CONFIDENTIALITY OF BUSINESS INFORMATION	38
9.3.1	<i>Scope of Confidential Information</i>	38
9.3.2	<i>Information Outside Scope of Confidential Information</i>	38
9.3.3	<i>Responsibility of Protecting Confidential Information</i>	38
9.4	PROTECTION OF PERSONAL INFORMATION	39
9.4.1	<i>Privacy Policy</i>	39
9.4.2	<i>Information Handled as Personal Information</i>	39
9.4.3	<i>Information not Deemed Personal Information</i>	39
9.4.4	<i>Responsibility of Protecting Personal Information</i>	39
9.4.5	<i>Notification to and Consent from Individuals on Use of Personal Information</i>	39
9.4.6	<i>Disclosure based on Judicial or Administrative Procedures</i>	39
9.4.7	<i>Other Cases of Information Disclosure</i>	39
9.5	INTELLECTUAL PROPERTY RIGHTS	39
9.6	REPRESENTATIONS AND WARRANTIES	40
9.6.1	<i>Representations and Warranties of Issuing Authority</i>	40
9.6.2	<i>Representations and Warranties of Registration Authority</i>	40

9.6.3	<i>Representations and Warranties of Subscribers</i>	40
9.6.4	<i>Representations and Warranties of Relying Parties</i>	41
9.6.5	<i>Representations and Warranties of Other Relevant Parties</i>	41
9.7	DISCLAIMERS OF WARRANTIES	41
9.8	LIMITATIONS OF LIABILITY	41
9.9	INDEMNITIES.....	42
9.10	TERM OF DOCUMENT AND TERMINATION	42
9.10.1	<i>Term of Document</i>	42
9.10.2	<i>Termination</i>	42
9.10.3	<i>Influence of Termination and Surviving Provisions</i>	42
9.11	INDIVIDUAL NOTICES AND COMMUNICATIONS WITH PARTICIPANTS.....	42
9.12	AMENDMENTS	42
9.12.1	<i>Amendment Procedures</i>	42
9.12.2	<i>Notification Method and Period</i>	42
9.12.3	<i>Change of Object Identifier</i>	42
9.13	DISPUTE RESOLUTION PROCEDURES	43
9.14	GOVERNING LAW.....	43
9.15	COMPLIANCE WITH APPLICABLE LAW	43
9.16	MISCELLANEOUS PROVISIONS	43
9.16.1	<i>Entire Agreement</i>	43
9.16.2	<i>Assignment of Rights</i>	43
9.16.3	<i>Severability</i>	43
9.16.4	<i>Enforceability</i>	43
9.16.5	<i>Force Majeure</i>	43
9.17	OTHER PROVISIONS.....	43
APPENDIX A: LIST OF DEFINITIONS		44
APPENDIX B: PROFILE OF CERTIFICATES		47

1. Introduction

1.1 Overview

Cybertrust Japan Co., Ltd. ("Cybertrust") operates the JCSI Root Certification Authority (the "Root CA").

The Root CA is a publicly trusted Root CA that is identified with the following Certification Authority name, serial number, effective period and other information, and Cybertrust started operating the Root CA from the following launch date.

Name of Certification Authority	SecureSign RootCA11
Launch Date of Certification Authority	June 30, 2014
Serial Number of Certification Authority Certificate	01
Validity Period of Certification Authority Certificate	April 8, 2009 to April 8, 2029
Signature Algorithm	SHA1 with RSA
Key Length of Certification Authority	2048 bit
Hash value (SHA-1)	3BC49F48F8F373A09C1E BDF85BB1C365C7D811B3
Hash value (SHA-256)	BF0FEEFB9E3A581AD5F9 E9DB7589985743D26108 5C4D314F6F5D7259AA42 1612

Note that the key pair and root certificate of the Root CA were created on April 8, 2009 by Japan Certification Services, Inc.(*) ("JCSI"), and were acquired by Cybertrust after JCSI terminated the provision of its services using the foregoing the Root CA Certificate in 2014. With regard to JCSI's services and contents that were provided based on such services (including, but not limited to, certificates issued before June 30, 2014 to be chained to the foregoing the Root CA Certificate and revocation information, and related materials, contracts, and correspondences), JCSI was liable for such services and contents, and the Cybertrust has no knowledge of the same and is not liable therefor. Cybertrust is not JCSI's agent, trustee or any other representative.

(*) JCSI became a corporation in liquidation as of June 30, 2013. As of May 2014, JCSI's head office was located at Akasaka No. 1 Bldg. 4F, 4-9-17 Akasaka, Minato-ku, Tokyo 107-0052. After then, JCSI was completely liquidated as of February 26, 2015 and terminated as company.

The Root CA issues certificates (the "Subordinate CA Certificate") of a JCSI Subordinate CA (the "Subordinate CA"; and the entity operating the Subordinate CA is hereinafter referred to as the "Subordinate CA Operator") that issues JCSI SSL/TLS certificates to subscribers, where JCSI SSL/TLS Certificate is an SSL/TLS server certificate (the "Subscriber Certificate") for use in certifying servers and network devices upon performing SSL/TLS communication. As set forth in List of Definition, Subordinate CA is provided to the Subordinate CA Operator as the "JCSI certificate issuing service" ("this service"); and the Subordinate CA Operator is the same organization with Subscribers due to the characteristics of this service.

With the approval of Root CA Supervisor, the Root CA issues an OSCP server certificate that appends the digital signature to OSCP responses when the Root CA provides revocation information with regards to the Subordinate CA based on OSCP.

Furthermore, with the approval of Subordinate CA Supervisor, the Subordinate CA issues an OSCP server certificate that appends the digital signature to OSCP responses when the Subordinate CA provides revocation information with regards to the Subscriber Certificates based on OSCP.

The Root CA and the Subordinate CA (unless separately provided for herein, collectively, the "Certification Authorities") are based on the following statement and laws and ordinances:

- (i) Current version of the guideline “Baseline Requirements for the Issuance and Management of Publicly-Trusted Certificates” (the “BR”) currently formulated by the CA/Browser Forum (the “CAB Forum”).
- (ii) this CPS; and
- (iii) laws of Japan that are applicable to the operations to be performed by the Certification Authority established in Japan.

The Certification Authorities complies with the latest version of the BR. If any inconsistency exists between this CPS and the BR, the BR have precedence of this CPS.

This CPS prescribes the operation of the Root CA on and after the launch date as well as the various requirements pertaining thereto, the operation of the Subordinate CA as well as the various requirements pertaining thereto, and the requirements for the Subordinate CA to issue certificates. The requirements include obligations of the Certification Authorities, obligations of the subscribers, and obligations of the relying parties.

Upon specifying the various requirements in this CPS, the RFC3647 "Certificate Policy and Certification Practices Framework" set forth by the IETF PKIX Working Group shall be adopted. RFC3647 is an international guideline that sets forth the framework of CPS or CP. Matters that do not apply to the Certification Authorities in the respective provisions of this CPS provided based on the framework of RFC3647 are indicated as "Not applicable".

The Subordinate CA does not individually prescribe a policy for each subscriber certificate ("CP"), and this CPS shall include the respective CPs.

1.2 Document Name and Identification

The official name of this CPS shall be the "JCSI Root CA Certification Practice Statement".

The object identifier (OID) to be assigned to this CPS and related services shall be as follows.

OID	Object
1.2.392.00200081.1.10.10	Cybertrust Japan JCSI Root Certification Authority Certificate Policy: PolicyIdentifier

1.3 PKI Participants

The PKI Participants described in this CPS are set forth below. Each of the relevant parties must observe the obligations set forth in this CPS.

1.3.1 Certification Authority

The Root CA and Subordinate CA set forth in "1.1 Overview" of this CPS. The Certification Authority is composed from an Issuing Authority and a Registration Authority. The Certification Authority shall be governed by the Certification Authority Supervisor set forth in "5.2.1 Trusted Roles and Personnel" of this CPS, and Cybertrust Japan Policy Authority("CTJ PA") approves this CPS.

1.3.2 Registration Authority

The Registration Authority ("RA") of the Root CA is operated by Cybertrust, and accepts applications for this service, and screens the applications based on this CPS. Based on the screening results, the Registration Authority instructs the Issuing Authority of the Root CA to issue or revoke the Subordinate CA Certificate, or dismisses the applications. Cybertrust does not delegate its RA operation to any of third parties.

The RA of the Subordinate CA is operated by the same organization with the Subscriber, and accepts applications for certificates from subscriber, and screens the applications based on this CPS. Based on the screening results, the Registration Authority instructs the Issuing Authority of the Subordinate CA to issue or revoke the Subscriber Certificate, or dismisses the applications. Cybertrust does not allow the Subordinate CA Operator to delegate its RA operation to any of third parties.

1.3.3 Issuing Authority

The Issuing Authority of the Root CA is operated by Cybertrust, and issues or revokes Subordinate certificates based on instructions from the Registration Authority of the Root CA. The Issuing Authority also controls the private key of the Root CA based on this CPS.

The Issuing Authority of the Subordinate CA is provided by Cybertrust in this service, and issues or revokes Subscriber Certificates based on instructions from the Registration Authority of the Subordinate CA. The Issuing Authority also controls the private key of the Subordinate CA based on this CPS.

1.3.4 Subscribers

A subscriber is an organization that applies for a certificate with the Subordinate CA, and uses the Subscriber Certificate based on this CPS and the subscriber agreement.

A person who is responsible for applying for a Subscriber Certificate is referred to as an application supervisor. A subscriber must appoint an application supervisor among persons affiliated with the subscriber's organization.

Persons affiliated with the subscriber who may apply for a certificate with the Subordinate CA shall be limited to the application supervisor, or a procedural manager who is authorized by the application supervisor to submit an application. The procedural manager may be appointed among persons inside the subscriber's organization.

1.3.5 Relying Parties

A relying party is an organization or an individual that verifies the validity of the certificates of the Certification Authorities and the subscribers, and relies on the certificates of the Certification Authorities and the subscribers based on one's own judgment.

1.3.6 Other Relevant Parties

Not applicable.

1.4 Certificate Usage

1.4.1 Types of Certificates

1.4.1.1 Root CA Certificate

The certificate shown in Appendix B of this CPS is a Root CA certificate.

1.4.1.2 Subordinate CA Certificate

A Subordinate CA Certificate is the certificate of the Subordinate CA issued under the Root CA in this service.

Upon issuing a Subordinate CA Certificate, the Registration Authority of the Root CA shall screen the following matters based on this CPS:

- (i) legal or physical existence of subscribers and the appropriate value of Distinguished Name ("DN") is applied;
- (ii) a subscriber has the right to use the Fully-Qualified Domain Name ("FQDN") assigned in the permitted DNS Name of the NameConstraints extension in the Subordinate CA Certificate;
- (iii) employment of an application supervisor;
- (iv) acceptance of the subscriber agreement;
- (v) approval of the application supervisor for the procedural manager to submit an application; and
- (vi) high risk status, etc.*

*The following will be surveyed as the high-risk status, etc.:

- past fishing cases; and
- records of applications that were dismissed or records of Subordinate CA Certificates that were revoked by the Root CA in the past due to suspicion of fishing and other fraudulent acts (if present).

If there is suspicion based on the foregoing survey, the Root CA shall perform additional screening that it deems appropriate as needed.

1.4.1.3 Subscriber Certificates

The Subordinate CA issues a Certificate to subscribers.

The Subscriber Certificate certifies a subscriber's server or network device, and realizes the SSL/TLS encrypted communication between such server or network device and a relying party's client device. Upon issuing a Subscriber Certificate, the Registration Authority of the Subordinate CA shall screen the following matters based on this CPS when the subscriber agreement is continued and active (subscriber uses this service continuously):

- (i) legal or physical existence of subscribers;
- (ii) a subscriber has the right to use the Fully-Qualified Domain Name ("FQDN") included in the Subscriber Certificate and shall not conflict with the NameConstraints;
- (iii) employment of an application supervisor;
- (iv) approval of the application supervisor for the procedural manager to submit an application; and
- (v) high risk status, etc.*

*The following or additional verification as reasonably necessary will be surveyed as the high-risk status:

- past fishing cases; and
- records of applications that were dismissed or records of the Subscriber Certificates that were revoked by the Subordinate CA in the past due to suspicion of fishing and other fraudulent acts.

If there is suspicion of fraudulent use of a certificate for which an application was submitted with the Subordinate CA based on the foregoing survey, the Subordinate CA shall perform additional screening that it deems appropriate as needed.

Note that the Subscriber Certificate shall be include no OU in this service.

And no EV SSL/TLS certificate is issued under the Root CA.

1.4.1.4 OCSP Server Certificate

OCSP server certificate is a certificate for OCSP response that the Certification Authorities issue and use. OCSP server certificate appends the digital signature to OCSP responses when the Certification Authority provides revocation information with regard to the Certification Authority based on OCSP.

1.4.2 Appropriate Certificate Usage

Uses of a certificate shall be as set forth below.

- (1) Subscriber Certificate
 - (i) Certification of devices (server, network device, etc.) in which the Certificate is to be used
 - (ii) SSL or TLS encrypted communication
- (2) OCSP Server Certificate
 - (i) Digital signing to OCSP responses providing revocation information

(3) Subordinate CA Certificate

- (i) Issuing a Subscriber Certificate to Subscriber who owns a domain name set forth in NameConstraints
- (ii) Issuing an OCSP Server Certificate which is for the OCSP responder providing revocation information of the Subscriber Certificates

1.4.3 Prohibited Certificate Usage

The use of certificates for any purpose other than as set forth in "1.4.2 Appropriate Certificate Usage" of this CPS shall be prohibited.

1.5 Policy Administration**1.5.1 Organization to Control Documents**

This CPS and the subscriber agreement are controlled by the CTJ PA.

1.5.2 Contact Point

The inquiries related to this CPS and other related matters are accepted at the following contact information.

This contact point is specified in the repositories and it shall be indicated that the inquiries are accepted 24 hours a day, 365 days a year.

Contact Information

Cybertrust Japan Co., Ltd., JCSI Root Support

Address: ARK Hills Sengokuyama Mori Tower 35F,
1-9-10 Roppongi, Minato-ku, Tokyo 106-0032

Email Address: jcsi-r@cybertrust.ne.jp

Inquiries and complaints:

- Inquiries regarding the application process for issuance and technical inquiries
- Inquiries regarding revocation requests and application process
- Inquiries regarding problems with certificates or upon discovery of fraudulent certificates
- Communication of other complaints
- Other inquiries regarding this CPS, etc.

1.5.3 Party to Determine Suitability of CPS

Cybertrust determines the suitability of this CPS.

1.5.4 Suitability Approval Procedures

The suitability of this CPS is approved by the CTJ PA during the assessment/approval procedures set forth in Cybertrust's internal rules and regulations.

1.6 Definitions and Acronyms

As prescribed in Appendix A of this CPS.

2. Publication and Repository Responsibilities

2.1 Organization to Operate Repositories

Repositories are controlled by Cybertrust.

2.2 Information to be Published

The repositories are published as follows.

Publish the following information on <https://www.cybertrust.co.jp/jcsi/repository.html>

- this CPS

Note that the subscriber agreement is disclosed to the applicant of this service by the JCSI Root Support.

Publish the following information on
<http://rtcr1.managedpki.ne.jp/SecureSignAD/SecureSignRootCA11/SSAD-rca.crt>

- Root CA Certificate

Publish the following information on
<http://rtcr1.managedpki.ne.jp/SecureSignAD/SecureSignRootCA11/cdp.crl>

- CRL issued by the Root CA

2.3 Timing and Frequency of Publication

The timing and frequency of publication shall be as follows; save for cases where repository maintenance or the like is required, but CRL shall be published 24 hours:

- (i) this repository shall be maintained available in public 24 hours a day, 365 days a year;
- (ii) this CPS shall be published each time it is amended;
- (iii) the CRL shall be updated as prescribed in "4.9.7 CRL Issue Cycle" of this CPS and the published; and
- (iv) the Root CA Certificate shall be published at least during the operation period of this Root CA.

2.4 Access Control on Repositories

The special access control on the repositories shall not be performed.

3. Identification and Authentication

3.1 Naming

3.1.1 Types of Names

Subscribers are identified based on the X.500 Distinguished Name ("DN") in the certificate.

3.1.2 Need for Names to be Meaningful

The name included in the DN of the certificate shall have the meaning of the subsequent paragraph.

DN Item	Meaning
Common Name	Name of Subordinate CA, or complete host name of server or network device to use the Subscriber Certificate
Organization	Name of organization of the Subscriber
Organization Unit	(Usage prohibited in this service.)
Locality	Address of business location of the Subscriber (locality)
State or Province	Address of business location of the Subscriber (state or province)
Country	Address of business location of the Subscriber (country)

3.1.3 Requirements for Anonymity or Pseudonymity of Subscribers

The Certification Authorities do not accept any certificate request by anonymity or pseudonymity of subscriber.

3.1.4 Rules for Interpreting Various Name Forms

Rules for interpreting the DN form of certificates issued by the Certification Authorities shall be pursuant to X.500.

3.1.5 Uniqueness of Names

The certificates issued by the Certification Authorities can uniquely identify a subscriber based on the DN.

3.1.6 Recognition, Authentication, and Role of Trademarks

The Certification Authorities do not authenticate the copyrights, trade secrets, trademark rights, utility model rights, patent rights and other intellectual property rights (including, but not limited to, rights for obtaining patents and other intellectual properties; simply "Intellectual Property Rights") upon issuing a certificate.

3.2 Initial Identity Validation

3.2.1 Method to Prove Possession of Private Key

A certificate signing request ("CSR") which constitutes a part of the application information from a subscriber includes a digital signature encrypted with a public key and a private key corresponding to the public key.

The Subordinate CA verifies the digital signature by using the public key included in the CSR and thereby validate that the digital signature was signed using the subscriber's private key, and determine that the subscriber is in possession of the private key.

Based on the usage of this service, the Root CA shall deem that the Subordinate CA Operator has become the Manager of Subordinate CA's private key.

3.2.2 Authentication of Organization and Domain Identity

3.2.2.1 Identity

The Certification Authorities shall screen and verify the matters set forth in “1.4.1 Types of Certificates” of this CPS.

Upon verifying the subscriber, the Certification Authorities shall use public documents and data, documents and data provided by a third party that is deemed reliable by the Certification Authorities, or documents and data provided by the subscriber, as well as make inquiries to an appropriate individual affiliated with the subscriber or the organization configuring the subscriber. Moreover, the Certification Authorities shall visit the subscriber and conduct an on-site survey as needed.

However, when there are documents or data that had been received from the subscriber or documents or data that had been independently obtained by the Certification Authorities during the period notified to the subscriber, and such documents or data have been screened successfully by the Certification Authorities, the Certification Authorities shall not request the resubmission of such documents or data.

Details regarding the verification procedures to be requested to subscribers shall be notified individually to the subscribers.

Note that it shall not be allowed for the subscriber to get and use a Certificate with a domain name owned by a third party other than the subscriber in this service.

3.2.2.2 DBA/Tradename

The Certification Authorities do not allow DBA / Tradename to be included in the Subscriber Certificate.

3.2.2.3 Verification of Country

The Certification Authorities confirm the Country included in the Subscriber Certificate with this CPS “3.2.2.1 Identity”.

3.2.2.4 Validation of Domain Authorization or Control

The Root CA shall confirm that prior to issuance the Subordinate CA Certificate, the Root CA has validated each Fully-Qualified Domain Name (FQDN) listed in the Subordinate CA Certificates via dNSNames in permittedSubtrees within the NameConstraints extension using at least one of the methods listed below.

The Subordinate CA shall confirm that prior to issuance the Certificate, the Subordinate CA has validated each Fully-Qualified Domain Name (FQDN) listed in Subscriber Certificates using dNSNames in the subjectAltName extension using at least one of the methods listed below.

Completed validations of Applicant authority may be valid for the issuance of multiple Subscriber Certificates over time. In all cases, the validation must have been initiated within the time period specified in the relevant requirement (such as Section 4.2.1 of BR) prior to Subscriber Certificate issuance. For purposes of domain validation, the term Applicant include the Applicant's Parent Company, Subsidiary Company, or Affiliate.

The Certification Authorities shall maintain a record of which domain validation method, including relevant BR version number, they used to validate every domain.

Note: FQDNs may be listed in Subscriber Certificates using dNSNames in the subjectAltName extension or in Subordinate CA Certificates via dNSNames in permittedSubtrees within the NameConstraints extension.

And the Certification Authorities shall not delegate the validation of the domain names to any third party.

3.2.2.4.1 Validating the Applicant as a Domain Contact

Note that the Certification Authorities shall not use this method set forth in BR 3.2.2.4.1.

3.2.2.4.2 Email, Fax, SMS, or Postal Mail to Domain Contact

The Certification Authorities shall confirm the Applicant's control over the FQDN by sending a Random Value via email, fax, SMS, or postal mail and then receiving a confirming response utilizing the Random Value. The Random Value must be sent to an email address, fax/SMS number, or postal mail address identified as a Domain Contact.

Each email, fax, SMS, or postal mail may confirm control of multiple Authorization Domain Names.

The Certification Authorities may send the email, fax, SMS, or postal mail identified under this section to more than one recipient provided that every recipient is identified by the Domain Name Registrar as representing the Domain Name Registrant for every FQDN being verified using the email, fax, SMS, or postal mail.

The Random Value shall be unique in each email, fax, SMS, or postal mail.

The Certification Authorities may resend the email, fax, SMS, or postal mail in its entirety, including re-use of the Random Value, provided that the communication's entire contents and recipient(s) remain unchanged.

The Random Value shall remain valid for use in a confirming response for no more than 30 days from its creation.

Note: Once the FQDN has been validated using this method, the Subordinate CA may also issue the Subscriber Certificates for other FQDNs that end with all the labels of the validated FQDN. This method is suitable for validating Wildcard Domain Names.

3.2.2.4.3 Phone Contact with Domain Contact

Certification Authorities shall not perform validations using this method set forth below after May 31, 2019. Completed validations using this method shall continue to be valid for subsequent issuance per the applicable certificate data reuse periods.

The Certification Authorities shall confirm the Applicant's control over the FQDN by calling the Domain Name Registrant's phone number and obtaining a response confirming the Applicant's request for validation of the FQDN. The Certification Authorities must place the call to a phone number identified by the Domain Name Registrar as the Domain Contact.

Each phone call shall be made to a single number and may confirm control of multiple FQDNs, provided that the phone number is identified by the Domain Registrar as a valid contact method for every Base Domain Name being verified using the phone call.

Note: Once the FQDN has been validated using this method, the Subordinate CA may also issue the Subscriber Certificates for other FQDNs that end with all the labels of the validated FQDN. This method is suitable for validating Wildcard Domain Names.

3.2.2.4.4 Constructed Email to Domain Contact

The Certification Authorities shall confirm the Applicant's control over the FQDN by (i) sending an email to one or more addresses created by using 'admin', 'administrator', 'webmaster', 'host master', or 'postmaster' as the local part, followed by the at sign ("@"), followed by an Authorization Domain Name, (ii) including a Random Value in the email, and (iii) receiving a confirming response utilizing the Random Value.

Each email may confirm control of multiple FQDNs, provided the Authorization Domain Name used in the email is an Authorization Domain Name for each FQDN being confirmed

The Random Value shall be unique in each email.

The email may be re-sent in its entirety, including the re-use of the Random Value, provided that its entire contents and recipient shall remain unchanged.

The Random Value shall remain valid for use in a confirming response for no more than 30 days from its creation.

Note: Once the FQDN has been validated using this method, the Subordinate CA may also issue the Subscriber Certificates for other FQDNs that end with all the labels of the validated FQDN. This method is suitable for validating Wildcard Domain Names.

3.2.2.4.5 Domain Authorization Document

Note that the Certification Authorities shall not use this method set forth in BR 3.2.2.4.5.

3.2.2.4.6 Agreed-Upon Change to Website

The Certification Authority shall confirm the Applicant's control over the FQDN by confirming one of the following under the "/.wellknown/pki-validation" directory, or another path registered with IANA for the purpose of Domain Validation, on the Authorization Domain Name that is accessible by the Certification Authorities via HTTP/HTTPS over an Authorized Port:

- (i) The presence of Required Website Content contained in the content of a file. The entire Required Website Content must not appear in the request used to retrieve the file or web page, or
- (ii) The presence of the Request Token or Request Value contained in the content of a file where the Request Token or Random Value must not appear in the request.

If a Random Value is used, the Certification Authority shall provide a Random Value unique to the Subscriber Certificate request and shall not use the Random Value after the longer of (i) 30 days or (ii) if the Applicant submitted the Certification Authority request, the timeframe permitted for reuse of validated information relevant to the Certification Authority (such as in BR 4.2.1).

However, the Subordinate CA with nameConstraints shall not adopt Request Token.

3.2.2.4.7 DNS Change

The Certification Authorities shall confirm the Applicant's control over the FQDN by confirming the presence of a Random Value or Request Token for either in a DNS CNAME, TXT or CAA record for either 1) an Authorization Domain Name; or 2) an Authorization Domain Name that is prefixed with a label that begins with an underscore character.

If a Random Value is used, the Certification Authorities shall provide a Random Value unique to the Certificate request and shall not use the Random Value after (i) 30 days or (ii) if the Applicant submitted the Certificate request, the timeframe permitted for reuse of validated information relevant to the Certificate (such as in BR 3.3.1).

3.2.2.4.8 IP Address

The Root CA does not allow to issue the Subscriber Certificate with an IPAddress under the Root CA and it specifies excludedSubtrees of any IP addresses within the NameConstraints extension in the Subordinate CA Certificate.

3.2.2.4.9 Test Certificate

The Certification Authorities do not adopt this method set forth in BR 3.2.2.4.9.

3.2.2.4.10 TLS Using a Random Number

The Certification Authorities do not adopt this method set forth in BR 3.2.2.4.10.

3.2.2.4.11 Any Other Method

The Certification Authorities shall not use this method set forth in BR 3.2.2.4.11.

3.2.2.4.12 Validating Applicant as a Domain Contact

The Certification Authorities do not adopt this method set forth in BR 3.2.2.4.12.

3.2.2.4.13 Email to DNS CAA Contact

The Certification Authorities do not adopt this method set forth in BR 3.2.2.4.13.

3.2.2.4.14 Email to DNS TXT Contact

The Certification Authorities do not adopt this method set forth in BR 3.2.2.4.14.

3.2.2.4.15 Phone Contact with Domain Contact

Confirm the Applicant's control over the FQDN by calling the Domain Contact's phone number and obtain a confirming response to validate the Authorization Domain Name. Each phone call may confirm control of multiple Authorization Domain Names provided that the same Domain Contact phone number is listed for each Authorization Domain Name being verified and they provide a confirming response for each Authorization Domain Name. In the event that someone other than a Domain Contact is reached, the Certification Authorities may request to be transferred to the Domain Contact. In the event of reaching voicemail, the Certification Authorities may leave the Random Value and the Authorization Domain Name(s) being validated. The Random Value must be returned to the Certification Authorities to approve the request. The Random Value shall remain valid for use in a confirming response for no more than 30 days from its creation.

Note: Once the FQDN has been validated using this method, the Subordinate CA may also issue the Subscriber Certificates for other FQDNs that end with all the labels of the validated FQDN. This method is suitable for validating Wildcard Domain Names.

3.2.2.4.16 Phone Contact with DNS TXT Record Phone Contact

Confirm the Applicant's control over the FQDN by calling the DNS TXT Record Phone Contact's phone number and obtain a confirming response to validate the Authorization Domain Name. Each phone call may confirm control of multiple Authorization Domain Names provided that the same DNS TXT Record Phone Contact phone number is listed for each Authorization Domain Name being verified and they provide a confirming response for each Authorization Domain Name. The Certification Authorities may not knowingly be transferred or request to be transferred as this phone number has been specifically listed for the purposes of Domain Validation. In the event of reaching voicemail, the Certification Authorities may leave the Random Value and the Authorization Domain Name(s) being validated. The Random Value must be returned to the Certification Authorities to approve the request. The Random Value shall remain valid for use in a confirming response for no more than 30 days from its creation.

Note: Once the FQDN has been validated using this method, the Subordinate CA may also issue the Subscriber Certificates for other FQDNs that end with all the labels of the validated FQDN. This method is suitable for validating Wildcard Domain Names.

3.2.2.5 Authentication for an IP Address

The Root CA does not allow to issue the Subscriber Certificate with an IPAddress under the Root CA and it specifies excludedSubtrees of any IP addresses within the NameConstraints extension in the Subordinate CA Certificate.

3.2.2.6 Wildcard Domain Validation

Before issuing a Subscriber Certificate with a wildcard character (*) in a CN or subjectAltName of type DNS-ID, the Subordinate CA must determine if the wildcard character occurs in the first label position to the left of a "registry-controlled" label or "public suffix" (e.g. "*.com", "*.co.uk", see RFC 6454 Section 8.2 for further explanation). Determination of registry control shall follow practices as set forth in BR 3.2.2.6.

If a wildcard would fall within the label immediately to the left of a registry-controlled or public suffix, the Subordinate CA must refuse issuance unless the applicant proves its rightful control of the entire Domain Namespace.

3.2.2.7 Data Source Accuracy

Prior to using any data source as a Reliable Data Source, the Certification Authorities shall evaluate the source for its reliability, accuracy, and resistance to alteration or falsification. The Certification Authorities consider the following during its evaluation:

- (i) The age of the information provided,
- (ii) The frequency of updates to the information source,
- (iii) The data provider and purpose of the data collection,
- (iv) The public accessibility of the data availability, and
- (v) The relative difficulty in falsifying or altering the data.

Databases maintained by the Certification Authorities, its owner, or its affiliated companies do not qualify as a Reliable Data Source if the primary purpose of the database is to collect information for the purpose of fulfilling the validation requirements under this Section 3.2.

3.2.2.8 CAA Record (Certification Authority Authorization Record) Procedures

The Root CA shall deem that a subscriber has designated the Subordinate CA, the Technically Constrained Subordinate CA, as a certificate authority that permits issuances of Subscriber certificates when the subscriber submits this service to be provided the Subordinate CA. And the Root CA shall not verify the CAA Record when the Root CA issues the Subordinate CA Certificate. Similarly, the Subordinate CA does not verify the CAA Record since the CAA checking is optional for certificates issued by a Technically Constrained Subordinate CA as set forth in BR 3.2.2.8.

Note that the Subordinate CA which is not Technically Constrained will verify the CAA Record set forth in RFC 6844(DNS Certification Authority Authorization (CAA) Resource Record) in accordance with the BR 3.2.2.8. If the CAA record (issue / issuewild) contains any values set forth in "4.2.1 Identity Validation and Execution of Certification Operations" of this CPS, this Subordinate CA recognizes that it is designated as a certificate authority that permits issuances of the certificates.

3.2.3 Authentication of Individual Identity

The Subordinate CA shall not issue a certificate to an individual.

3.2.4 Non-verified Subscriber Information

Not applicable.

3.2.5 Verification of Application Supervisor

The Certification Authorities shall verify the employment of the application supervisor and the authority to submit an application on behalf of the subscriber. The Certification Authorities shall additionally verify that the application supervisor has accepted the subscriber agreement and approved the filing of an application by the procedural manager by way of call-back or means equivalent to call-back. The phone number to be used for the call-back shall be a number provided by a third party or a number included in the documents or data which were provided by the subscriber and have been deemed to be reliable by the Certification Authorities.

3.2.6 Interoperability Standards

Not applicable.

3.3 Identification and Authentication for Key (Certificate) Renewal Request

3.3.1 Identification and Authentication upon Renewal for Routine Key (Certificate) Renewal

The provisions of "3.2 Initial Identity Validation" of this CPS shall apply correspondingly.

3.3.2 Identification and Authentication for Renewal of Key (Certificate) after Revocation

To be performed based on the same procedures as "3.2 Initial Identity Validation" of this CPS.

However, when it is verified that the public key, certification information and expiration date included in the CSR of the re-issuance application coincide with the certificate of the re-issuer, verification based on "3.2 Initial Identity Validation" of this CPS will not be performed, and a certificate shall be issued based on the verification of the foregoing coincidence.

3.4 Identity Validation and Authentication upon Revocation Request

When the Subordinate CA receives a revocation request from a subscriber via email, the Subordinate CA shall verify the identity of the person who submitted the application, that such person is authorized to submit an application, and the reason of revocation. As the verification method, the Subordinate CA shall compare the information notified to the Subordinate CA upon application for issuance of a Subscriber Certificate and the information only known to the Subordinate CA and the Subscriber.

Upon receiving a revocation request for a certificate of a specific subscriber other than the subscriber of that Certificate, the Certification Authority shall survey the reason of revocation and verify with the subscriber.

When the reason for revocation in the revocation request from a subscriber or a party other than that subscriber corresponds to a revocation event set forth in the subscriber agreement of the Certificate, the Certification Authority shall revoke the Certificate upon notifying the subscriber.

The email address to be used for the revocation request is indicated in "1.5.2 Contact Point" and Cybertrust's website.

4. Certificate Life-Cycle Operational Requirements

4.1 Certificate Application

4.1.1 Persons Who May Apply for Certificates

Persons who may apply with the Certification Authorities shall only be the application supervisor, or a procedural manager who was authorized by the application to supervisor submit an application.

Appointment of the application supervisor or the procedural manager shall be pursuant to the provisions of "1.3.4 Subscriber" of this CPS.

The Certification Authorities' verification of a subscriber's intent to submit an application shall be confirmed by the application supervisor or a person affiliated with the subscriber who was authorized by the application supervisor.

4.1.2 Enrolment Process and Responsibilities

A subscriber shall apply for this service upon accepting this CPS and the subscriber agreement. Upon filing an application, a subscriber is responsible for providing true and accurate information. The method of applying for this service shall be notified individually to the subscribers.

4.2 Certificate Application Processing

4.2.1 Identity Validation and Execution of Certification Operations

To be performed by the Registration Authority of the Certification Authorities based on the same procedures as "3.2 Initial Identity Validation" of this CPS.

If the CAA record (issue / issuewild) contains any of the following values, this Subordinate CA recognizes that it is designated as a certificate authority that permits issuances of the certificates.

* cybertrust.ne.jp

* jcsinc.co.jp

4.2.2 Approval or Rejection of Certificate Application

When all requirements prescribed in "3.2 Initial Identity Validation" of this CPS are confirmed, the Registration Authority of the Certification Authorities shall approve the application, and instruct the Issuing Authority to issue a certificate. The Certification Authorities shall never notify the subscriber of such issuance in advance.

Meanwhile, when the requirements prescribed in "3.2 Initial Identity Validation" of this CPS are not satisfied, the Certification Authorities shall dismiss the application for issuing a certificate, and reject issuance. In the foregoing case, the Certification Authorities shall notify the reason of such rejection to the application supervisor or the procedural manager who submitted the application. The Certification Authorities shall not return the information and data obtained from the application supervisor or the procedural manager during the application process.

When the application supervisor or the procedural manager withdraws the submitted application, the Certification Authorities shall dismiss such application. The Certification Authorities shall not return the information and data obtained from the application supervisor or the procedural manager during the application process.

4.2.3 Time Required for Certificate Application Procedures

After the Registration Authority of the Certification Authorities processes the application based on the provisions of "4.2 Certificate Application Procedures" of this CPS, the Issuing Authority shall issue a Certificate without delay.

4.3 Certificate Issuance

4.3.1 Certificate Issuance Procedures by Certification Authority

After completing the application procedures based on "3.2 Initial Identity Validation" of this CPS, the Registration Authority of the Certification Authorities shall instruct the Issuing Authority to issue the certificate. Simultaneously with issuing the certificate, the Issuing Authority shall send to the subscriber the notice.

4.3.2 Notification of Issuance of Certificate

Promptly after the certificate is issued, the Certification Authorities shall send to the subscriber the notice, and the procedures required for the subscriber to accept the certificate.

4.4 Certificate Acceptance

4.4.1 Certificate Acceptance Verification Procedures

A subscriber shall accept a Certificate according to the email sent from the Subordinate CA based on the provisions of "4.3.2 Notification of Issuance of Certificate" of this CPS. The Subordinate CA shall deem that a subscriber has accepted the certificate when the email is sent to the subscriber.

4.4.2 Publication of Certificate by Certification Authority

The Subordinate CA basically does not publish a Subscriber Certificate. However, the Subordinate CA may register and publish the Subscriber Certificates to CT log server, CCADB and so on.

4.4.3 Notification of Issuance of Certificate by Certification Authority to Other Participants

The Subordinate CA shall not notify the issuance of the Certificate to other participants based on "4.3.2 Notification of Issuance of Certificate" of this CPS.

4.5 Key Pair and Certificate Usage

4.5.1 Use of Private Key and Certificate by Subscriber

A subscriber shall use its private key and the Certificate only for the usage set forth in "1.4.2 Appropriate Certificate Uses" of this CPS, and use for any other usage is not allowed. Moreover, a subscriber's private key and the Certificate may only be used by the subscriber, and the subscriber must not license the use thereof to a third party. Other obligations of a subscriber regarding the use of its private key and the Certificate are set forth in "9.6.3 Representations and Warranties of Subscribers" of this CPS.

4.5.2 Use of Subscriber's Public Key and Certificate by Relying Party

A relying party shall confirm, under its own responsibility, the validity of the Certificate that is used by a subscriber for the usage set forth in "1.4.2 Appropriate Certificate Uses" of this CPS.

Other obligations of a relying party regarding the use of a subscriber's public key and the Certificate are set forth in "9.6.4 Representations and Warranties of Relying Parties".

4.6 Certificate Renewal Not Involving Key Renewal

4.6.1 Requirements for Certificate Renewal Not Involving Key Renewal

The Subordinate CA shall accept a renewal request pursuant to the expiration of the valid term of the Subscriber Certificate.

4.6.2 Persons Who May Request Renewal

The provisions of "4.1.1 Persons Who May Apply for Certificates" of this CPS shall apply correspondingly.

4.6.3 Renewal Request Procedures

The provisions of "4.2 Certificate Application Procedures" of this CPS shall apply correspondingly.

4.6.4 Notification of Issuance of Renewed Certificate

The provisions of "4.3.2 Notification of Issuance of Certificate" of this CPS shall apply correspondingly.

4.6.5 Procedures for Accepting Renewed Certificate

The provisions of "4.4.1 Certificate Acceptance Verification Procedures" of this CPS shall apply correspondingly.

4.6.6 Publication of Renewed Certificate

The provisions of "4.4.2 Publication of Certificate by Certification Authority" of this CPS shall apply correspondingly.

4.6.7 Notification of Issuance of Certificate by Certification Authority to Other Participants

The provisions of "4.4.3 Notification of Issuance of Certificate by Certification Authority to Other Participants" of this CPS shall apply correspondingly.

4.7 Certificate Re-Key

4.7.1 Requirements for Certificate Renewal Involving Rekey

The Subordinate CA shall accept a renewal request pursuant to the expiration of the valid term of the Certificate used by a subscriber.

4.7.2 Persons Who May Request Renewal

The provisions of "4.1.1 Persons Who May Apply for Certificates" of this CPS shall apply correspondingly.

4.7.3 Rekey Application Procedures

The provisions of "4.2 Certificate Application Procedures" of this CPS shall apply correspondingly.

4.7.4 Notification of Issuance of Rekeyed Certificate

The provisions of "4.3.2 Notification of Issuance of Certificate" of this CPS shall apply correspondingly.

4.7.5 Procedures for Accepting Rekeyed Certificate

The provisions of "4.4.1 Certificate Acceptance Verification Procedures" of this CPS shall apply correspondingly.

4.7.6 Publication of Rekeyed Certificate

The provisions of "4.4.2 Publication of Certificate by Certification Authority" of this CPS shall apply correspondingly.

4.7.7 Notification of Issuance of Rekeyed Certificate to Other Participants

The provisions of "4.4.3 Notification of Issuance of Certificate by Certification Authority to Other Participants" of this CPS shall apply correspondingly.

4.8 Modification of Certificate

4.8.1 Requirements for Modification of Certificate

The Subordinate CA shall not accept a request for modifying a previously issued Subscriber Certificate.

If there is any modification to the certificate information, a subscriber must promptly submit an application to the Subordinate CA for revoking the corresponding Subscriber Certificate.

4.8.2 Persons Who May Request Modification of Certificate

Not applicable.

4.8.3 Certificate Modification Procedures

Not applicable.

4.8.4 Notification of Issuance of Modified Certificate

Not applicable.

4.8.5 Procedures for Accepting Modified Certificate

Not applicable.

4.8.6 Publication of Modified Certificate

Not applicable.

4.8.7 Notification of Issuance of Modified Certificate to Other Participants

Not applicable.

4.9 Certificate Revocation and Suspension

4.9.1 Circumstance for Revocation

4.9.1.1 Reasons for Revoking a Subscriber Certificate

(1) Reason of Revocation by Subscriber

In the occurrence of any one of the following events, a subscriber must submit a request to the Subordinate CA for revoking the corresponding Subscriber Certificate:

- (i) a subscriber discovers a Subscriber Certificate that was issued based on an application for issuance that was not approved by the subscriber;
- (ii) a subscriber learns that its private key has been compromised or there is a possibility thereof;
- (iii) a subscriber learns of the unauthorized use of its private key or the Certificate or the possibility thereof;
- (iv) there is modification to the contents of a Subscriber Certificate;
- (v) a subscriber loses its right to exclusively use the FQDN included in the Subscriber Certificate;
- (vi) a subscriber discovers any values in conflict with the NameConstraints are included in the Subscriber Certificate;
- (vii) a subscriber discovers the Subscriber Certificate includes the organization unit (OU); or
- (viii) a subscriber wishes to cancel the subscriber agreement.

(2) Reason of Revocation by the Subordinate CA

Prior to revoking a Subscriber Certificate, the Subordinate CA verifies the identity and authority of the entity requesting revocation. The Subordinate CA will revoke a Certificate within 24 hours if one or more of the following occurs:

- (i) The Subscriber requests in writing that the Subordinate CA revoke the Subscriber Certificate;
- (ii) The Subscriber notifies the Subordinate CA that the original Certificate request was not authorized and does not retroactively grant authorization;
- (iii) The Subordinate CA obtains evidence that the Subscriber's Private Key corresponding to the Public Key in the Certificate suffered a Key Compromise; or
- (iv) The Subordinate CA obtains evidence that the validation of domain authorization or control for any FQDN in the Certificate should not be relied upon.

The Subordinate CA may revoke a Subscriber Certificate within 24 hours and must revoke a Subscriber Certificate within 5 days if one or more of the following occurs:

- (i) The Subscriber Certificate no longer complies with the requirements of BR 6.1.5 and BR 6.1.6;
- (ii) Cybertrust obtains evidence that the Subscriber Certificate was misused;
- (iii) a subscriber breaches a material obligation under this CPS or the subscriber agreement;
- (iv) Cybertrust confirms any circumstance indicating that use of a FQDN in the Subscriber Certificate is no longer legally permitted (e.g. a court or arbitrator has revoked a Domain Name registrant's right to use the Domain Name, a relevant licensing or services agreement between the Domain Name registrant and the Applicant has terminated, or the Domain Name registrant has failed to renew the Domain Name);
- (v) Cybertrust confirms that a subscriber's Wildcard Certificate has been used to authenticate a fraudulently misleading subordinate FQDN;
- (vi) Cybertrust confirms a material change in the information contained in the Subscriber Certificate;
- (vii) Cybertrust confirms that the Subscriber Certificate was not issued in accordance with the CA/B forum requirements or this CPS;
- (viii) Cybertrust confirms that, based on reasonable evidence, any of the information appearing in the Subscriber Certificate is inaccurate;
- (ix) The right of the Subordinate CA to issue the Subscriber Certificates under the CA/B forum requirements expires, is revoked or is terminated, unless the Subordinate CA has made arrangements to continue maintaining the CRL/OCSP Repository;
- (x) Revocation is required by this CPS; or
- (xi) Cybertrust confirms a demonstrated or proven method that exposes the Subscriber's Private Key to compromise, methods have been developed that can easily calculate it based on the Public Key (such as a Debian weak key, see <http://wiki.debian.org/SSLkeys>), or if there is clear evidence that the specific method used to generate the Private Key was flawed.

The Subordinate CA may revoke any Subscriber Certificates in its sole discretion, including if one or more of the following occurs:

- (i) Either the Subscriber's or Cybertrust's obligations under this CPS are delayed or prevented by circumstances beyond the party's reasonable control, including computer or communication failure, and, as a result, another entity's information is materially threatened or compromised;
- (ii) Cybertrust received a lawful and binding order from a government or regulatory body to revoke the Subscriber Certificate;
- (iii) The Subordinate CA ceased operations and did not arrange for another Certificate Authority to provide revocation support for the Certificates;

- (iv) The technical content or format of the Subscriber Certificate presents an unacceptable risk to application software vendors, Relying Parties, or others;
- (v) The Subscriber was added as a denied party or prohibited person to a blacklist;
- (vi) a subscriber fails to pay the fee of the Certificate in breach of Cybertrust's prescribed billing conditions;
- (vii) Cybertrust cancels the subscriber agreement with a subscriber based on the subscriber agreement; or
- (viii) the Subordinate CA learns that the private key of the Subordinate CA and/or the Root CA has been compromised or there is a possibility thereof.

4.9.1.2 Reasons for Revoking a Subordinate CA Certificate

In the occurrence of the following event, the Root CA shall revoke the corresponding Subordinate CA Certificate within seven (7) days at the time that such event is discovered:

- (i) The Subordinate CA requests revocation in writing;
- (ii) The Subordinate CA notifies the Root CA that the original application to this service was not authorized and does not retroactively grant authorization;
- (iii) The Root CA obtains evidence that the Subordinate CA's Private Key corresponding to the Public Key in the Subordinate CA Certificate suffered a Key Compromise or no longer complies with the requirements of BR 6.1.5 and BR 6.1.6;
- (iv) The Root CA obtains evidence that the Subordinate CA Certificate was misused;
- (v) The Root CA is made aware that the Certificate was not issued in accordance with or that Subordinate CA has not complied with the BR or the CPS;
- (vi) The Root CA determines that any of the information appearing in the Subordinate CA Certificate is inaccurate or misleading;
- (vii) The Root CA or the Subordinate CA ceases operations for any reason and has not made arrangements for another CA to provide revocation support for the Subscriber Certificate;
- (viii) The Root CA's or the Subordinate CA's right under these Requirements expires or is revoked or terminated, unless they have made arrangements to continue maintaining the CRL/OCSP Repository;
- (ix) Revocation of the Subordinate CA Certificate is required by the Root CA's CPS;
- (x) The technical content or format of the Certificate presents an unacceptable risk to Application Software Suppliers or Relying Parties; or
- (xi) Cybertrust terminates this service.

4.9.1.3 Reason of Revoking Other certificates

(1) Root CA Certificate

In the occurrence of any one of the following events, the Root CA revokes the Root CA Certificate at the time that such event is discovered; provided, however, that, with regard to (ii) below, the Root CA may revoke its certificate on a day that is separately notified by the Root CA before termination of operations:

- (i) when it is learned that the private key of the Root CA has been compromised; or
- (ii) when the Root CA is to terminate its certification operations.

(2) OCSP server Certificate

In the occurrence of any of the following events, the Certification Authorities revoke the corresponding OCSP server certificate at the time that such event is discovered:

- (i) when it is learned that the private key of an OCSP server certificate has been compromised; or
- (ii) when the Certification Authority is to terminate its certification operations.

4.9.2 Persons Eligible for Applying for Revocation

Persons who may request revocation shall be the application supervisor, the procedural manager.

4.9.3 Revocation Application Procedures

A subscriber shall submit a revocation request basically by email. The revocation request must include reason of revocation, contact information and so on. The Certification Authorities shall verify the reason of revocation.

The revocation of the Certification Authority certificate and the OCSP certificate shall be instructed by the Certification Authority Supervisor to the Issuing Authority.

4.9.4 Grace Period up to Revocation Application

In the occurrence of an event corresponding to "4.9.1.1 Reasons for Revoking a Subscriber Certificate" of this CPS, the Subscriber shall promptly submit a revocation request.

In the occurrence of an event corresponding to "4.9.1.2 Reasons for Revoking a Subordinate CA Certificate" or "4.9.1.3 Reason of Revocation Other certificates" of this CPS, the Certification Authority Supervisor shall promptly give revocation instructions.

4.9.5 Time Required for Certification Authority to Process Revocation

The Certification Authorities accept the revocation request 24/7.

Within 24 hours after receiving a Certificate Problem Report, the Certification Authorities shall investigate the facts and circumstances related to a Certificate Problem Report and provide a preliminary report on its findings to both the Subscriber and the entity who filed the Certificate Problem Report. After reviewing the facts and circumstances, the Certification Authorities shall work with the Subscriber and any entity reporting the Certificate Problem Report or other revocation-related notice to establish whether or not the certificate will be revoked, and if so, a date which the Certification Authorities will revoke the certificate. The period from receipt of the Certificate Problem Report or revocation-related notice to published revocation must not exceed the time frame set forth in Section 4.9.1.1. The date selected by the Certification Authorities should consider the following criteria:

- (i) The nature of the alleged problem (scope, context, severity, magnitude, risk of harm);
- (ii) The consequences of revocation (direct and collateral impacts to Subscribers and Relying Parties);
- (iii) The number of Certificate Problem Reports received about a particular Certificate or Subscriber;
- (iv) The entity making the complaint; and
- (v) Relevant legislation.

4.9.6 Revocation Confirmation Method by Relying Parties

The relying parties shall confirm the certificate revocation of the Certificate with the CRLs issued by the Certification Authorities or the OCSP servers.

4.9.7 CRL Issue Cycle

The Subordinate CA issues the CRL in a cycle of less than 24 hours.

The Root CA shall issue the CRL for each occurrence of an event corresponding to "4.9.1.2 Reasons for Revoking a Subordinate CA Certificate" or "4.9.1.3 Reason of Revocation Other certificates" of this CPS or once a year at least.

4.9.8 Maximum Delay Time up to CRL Publication

The validity period of the Subordinate CA's CRL is 168 hours.

The Subordinate CA shall publish each CRLs in the repositories no later than one (1) hour after the issuance thereof.

4.9.9 Online Confirmation of Revocation Information

OCSP responses conform to RFC 6960.

OCSP responses is signed by the OCSP Responder whose Certificate is signed by the Certification Authority that issued the Certificate whose revocation status is being checked.

The OCSP signing Certificate contains the extension of type id-pkix-ocsp-nocheck.

4.9.10 Online Certificate Revocation/Status Checking

The Certification Authorities supports an OCSP capability using the GET method.

The Certification Authorities shall provide revocation information based on OCSP, in addition to CRL.

The Subordinate CA shall renew the OCSP response, which has a valid term of 168 hours, in a cycle of less than 96 hours.

The Root CA shall provide revocation information of the Subordinate CA Certificate based on OCSP. The Root CA shall update the OCSP response at least one a year, or no later than 24 hours after it revokes a Subordinate CA Certificate.

The responder shall not respond with a "good" status. if the OCSP responder receives a request for status of a certificate that has not been issued.

The URL to accept OCSP requests in regard to the Root CA shall be as follows;

<http://rtocsp.managedpki.ne.jp/OcspServer>

4.9.11 Means for Providing Other Forms of Revocation Advertisements

Not applicable.

4.9.12 Special Requirements on Compromise of Key

4.9.12.1 Certificate

When the Subordinate CA learns that the Subscriber's private key has been compromised or there is a possibility thereof, the Subordinate CA shall take the revocation procedures of the Certificate based on "4.9.3 Revocation Application Procedures" of this CPS.

4.9.12.2 OCSP Server Certificate

When the Certification Authority learns that the private key of an OCSP server certificate has been compromised, the Certification Authority shall take the revocation procedures of the corresponding OCSP server certificate based on "4.9.3 Revocation Application Procedures" of this CPS.

4.9.13 Certificate Suspension Requirements

The Certification Authorities do not accept applications for suspending the Certificates.

4.9.14 Persons Eligible for Applying for Suspension

Not applicable.

4.9.15 Suspension Application Procedures

Not applicable.

4.9.16 Term of Suspension

Not applicable.

4.10 Certificate Status Services

The Certification Authorities shall not provide services that enable the verification of the certificate status other than by way of CRL and OCSP.

4.10.1 Operational Characteristics

Revocation entries on a CRL or OCSP Response shall not be removed until after the Expiry Date of the revoked Certificate.

4.10.2 Service Availability

The Certification Authorities shall operate and maintain its CRL and OCSP capability with resources sufficient to provide a response time of ten (10) seconds or less under normal operating conditions.

The Certification Authorities shall maintain an online 24x7 Repository that application software can use to automatically check the current status of all unexpired Certificates issued by the Certification Authorities.

The Certification Authorities shall maintain a continuous 24x7 ability to respond internally to a high-priority Certificate Problem Report, and where appropriate, forward such a complaint to CTJ PA, and/or revoke a Certificate that is the subject of such a complaint.

4.10.3 Other Requirements

Not applicable.

4.11 End of Subscription (Registration)

The reasons for ending the use of this service shall be set forth in the respective subscriber agreements. Moreover, if a subscriber wishes to terminate the subscriber agreement midway during the valid term of the certificate, the subscriber must submit a revocation request of the Subscriber Certificate with the Subordinate CA based on "4.9.3 Revocation Request Procedures" of this CPS.

4.12 Key Escrow and Recovery

4.12.1 Key escrow and recovery policy and practices

Not applicable.

4.12.2 Session key encapsulation and recovery policy and practices

Not applicable.

5. Management, Operational, And Physical Controls

5.1 Physical Security Construction

5.1.1 Site Location and Structure

The Certification Authority system shall be installed in a facility that is not easily affected by earthquakes, fires, floods and other disasters (the "Facility"; unless separately prescribed herein, the term "Facility" as used herein shall include the main site and the backup site set forth in "5.1.9 off-site backup " of this CPS). The Facility shall undergo architectural measures for preventing earthquakes, fires, floods and other disasters as well as preventing unauthorized invasion. Information regarding the location of the Certification Authority shall not be indicated outside or inside the building where the Facility is located.

5.1.2 Physical Access

The Facility and the respective rooms where certification operations are performed in the Facility shall be set with a security level according to the importance of the operation, and suitable entrance/exit control shall be performed. For authentication upon entering/existing the room, an entrance/exit card or biometric identification or other implementable technological means shall be used in accordance with the security level. For entry into particularly important rooms and one or both doors of the safe used for storing the Certification Authority system and other important assets in the same room, measures must be taken where the doors cannot be opened unless multiple persons with entrance authority are present.

The Facility and the respective rooms where certification operations are performed in the Facility shall be monitored with a monitoring system 24/7.

5.1.3 Power and Air-conditioning

In the Facility, power sources with necessary and sufficient capacity for operating the Certification Authority system and related equipment shall be secured. An uninterruptable power supply and a private power generator shall be installed as measures against instantaneous interruption and blackouts. Air-conditioning equipment shall be installed in the respective rooms where certification operations are performed, and this shall be duplicated in particularly important rooms.

5.1.4 Water-exposures Control Measures

A water leakage detector shall be installed in the particularly important rooms in the Facility where certification operations are performed, and waterproofing measures shall be taken.

5.1.5 Fire Control Measures

The Facility is of a fire-proof construction. The particularly important rooms are located within the fire-retarding division, and fire alarms and automatic gas fire extinguishers shall be installed.

5.1.6 Anti-earthquake Measures

The Facility is of an earthquake-resistant construction, and the equipment and fixtures of the Certification Authority system have undergone tip-prevention measures and anti-drop measures.

5.1.7 Medium Storage Site

Mediums containing the backup data of the Certification Authority system and forms and the like relating to the operation of the Certification Authority shall be stored in a room in which only authorized personnel can enter.

5.1.8 Waste Disposal

Documents containing Confidential Information shall be disposed after being shredded with a shredder. Electronic mediums shall be physically destroyed, initialized, demagnetized or subject to other similar measures to completely erase the recorded data before being discarded.

5.1.9 Off-site Backup

The original or copy of the private key of the Certification Authorities and important assets for system recovery shall be stored in the main site, and also in a remote backup site. The locking of the safe in the backup site shall be controlled by multiple persons, and the opening/closing of the safe shall be recorded.

5.2 Procedural Controls

5.2.1 Trusted Roles and Personnel

The Certification Authorities shall set forth the personnel required for operating the Certification Authorities (the "Certification Authority Staff") and their roles as follows.

5.2.1.1 Certification Authority Supervisor

The Certification Authority Supervisor shall govern the Certification Authority.

5.2.1.2 Issuing Authority Manager

The Issuing Authority Manager shall control the operations of the Issuing Authority of the Certification Authority.

5.2.1.3 Issuing Authority System Administrator

The Issuing Authority System Administrator shall maintain and control the Certification Authority system (issuing an OSCP server certificate or like that based on Certification Authority Supervisor's instructions including) under the control of the Issuing Authority Manager.

5.2.1.4 Issuing Authority Operator

The Issuing Authority Operator shall assist the operations of the Issuing Authority Manager and the Issuing Authority System Administrator; provided, however, that the Issuing Authority Operator is not authorized to operate the Certification Authority system.

5.2.1.5 Registration Authority Manager

The Registration Authority Manager shall control the operations of the Registration Authority of the Certification Authority.

5.2.1.6 Registration Authority Operator Manager

The Registration Authority Operator Manager shall control the Registration Authority Operator.

5.2.1.7 Registration Authority Operator

The Registration Authority Operator shall process the applications under the control of the Registration Authority Manager, and request the issuance or revocation of certificates to the Issuing Authority.

5.2.2 Number of Personnel Required for Each Role

The Certification Authorities shall respectively appoint two or more Issuing Authority System Administrators and Registration Authority Operators.

5.2.3 Personal Identification and Verification of Each Role

The Certification Authorities shall establish the entrance authority of the respective rooms where certification operations are performed and the operation authority of the Certification Authority system in accordance with the respective roles. For entry into the respective rooms and upon operation of the system, an entrance/exit card, biometric identification, digital certificate, ID and password are used independently or in combination to confirm and verify the identification and entrance/operation authority.

5.2.4 Roles Requiring Segregation of Duties

The Certification Authorities do not allow the concurrent serving of the Issuing Authority and the Registration Authority, and the Certification Authorities do not allow the Certification Authority Supervisor to concurrently serve another role.

5.3 Personnel Security Controls

5.3.1 Qualifications, Experience, Clearances

The Certification Authority Staff shall be hired and assigned based on the recruitment standards to be separately set forth by Cybertrust.

5.3.2 Background Checks and Clearance Procedures

The background check of employees to be assigned as the Certification Authority Staff shall be conducted based on Cybertrust's internal rules and regulations.

5.3.3 Training Requirements and Procedures

The Certification Authorities shall implement training requirements and procedures to all employees who will be assigned as the Certification Authority Staff. The training requirements and procedures shall include, in addition to the education of this CPS, the required training requirements and procedures in accordance with the role of the Certification Authority Staff.

The validity of the training requirements and procedures shall be evaluated by the Issuing Authority Manager or the Registration Authority Manager, and retraining shall be implemented as needed.

5.3.4 Retraining Period and Procedures

The Certification Authorities shall implement retraining requirements and procedures to the Certification Authority Staff as needed. In the least, the Certification Authorities shall implement training in the occurrence of the following events:

- (i) when this CPS is amended, and CTJ PA, the Certification Authority Supervisor, the Issuing Authority Manager or the Registration Authority Manager deems necessary;
- (ii) when the Certification Authority system is changed, and CTJ PA, the Certification Authority Supervisor, the Issuing Authority Manager or the Registration Authority Manager deems necessary; or
- (iii) when CTJ PA, the Certification Authority Supervisor, the Issuing Authority Manager, or the Registration Authority Manager otherwise deems necessary.

5.3.5 Frequency and Sequence for Job Rotation

The Certification Authorities shall rotate jobs of the Certification Authority Staff as needed.

5.3.6 Sanction against Unauthorized Actions

When a Certification Authority Staff conducts an act that is in breach of this CPS, Cybertrust shall promptly investigate the cause and scope of influence, and impose penalty on that Certification Authority Staff in accordance with Cybertrust's work rules.

5.3.7 Contract Requirements of Contract Employees

When Cybertrust is to assign employees of outsourcees, contract employees of dispatched employees (collectively, the "Contract Employees") as a Certification Authority Staff, Cybertrust shall conclude a contract that clearly sets forth the details of the outsourced work, confidentiality obligation to be imposed on the Contract Employees, and penal regulations, and demand the Contract Employees to observe this CPS and Cybertrust's internal rules and regulations. When the Contract Employees conduct an act that is in breach of this CPS and Cybertrust's internal rules and regulations, penalties shall be imposed based on the foregoing contract.

5.3.8 Documents Available to Certification Authority Staff

The Certification Authorities shall take measures so that the respective Certification Authority Staff can only refer to documents that are required according to their respective roles.

5.4 Audit Logging Procedures

5.4.1 Types of Events to be Recorded

In order to evaluate the compliance of this CPS and the suitability of security, the Certification Authorities shall collect the following records as monitoring logs. The records shall include the date and time, subject of the record, and description of event.

- (i) records of screenings performed by the Registration Authority;
- (ii) records of systems that are being maintained and controlled by the Registration Authority and the Issuing Authority;
- (iii) records regarding the network security;
- (iv) records regarding the entry/exit of the Facility; and
- (v) records regarding the maintenance and control of the Facility.

5.4.2 Audit Logging Frequency

The Certification Authorities shall inspect the monitoring logs prescribed in "5.4.1 Types of Events to be Recorded" of this CPS once a week, once a month, and once a quarter.

5.4.3 Audit Log Archival Period

Records of the screening performed by the Registration Authority shall be archived at least 7 years after the expiration of the effective period of the certificate that was issued based on the foregoing screening or during the operation period of the Certification Authorities, whichever comes first.

Other records shall be archived at least 7 years.

When the monitoring logs are no longer required, the Certification Authorities shall dispose such monitoring logs based on the provisions of "5.1.8 Waste Disposal" of this CPS.

5.4.4 Audit Log Protection

The Certification Authorities shall implement access control the monitoring logs so that only authorized personnel can peruse the monitoring logs. The Certification Authorities shall implement physical access control to the safe and logical access control to folders and the like in cases of electronic mediums.

5.4.5 Audit Log Backup Procedures

The Certification Authorities shall acquire the backup of logs in the systems of the Registration Authority and the Issuing Authority. For paper mediums, only the original copies thereof need to be archived.

5.4.6 Audit Log Collection System

Systems of the Registration Authority and the Issuing Authority shall automatically collect the monitoring logs based on the function installed in the system.

5.4.7 Notification to Parties

The Certification Authorities shall collect and inspect the monitoring log without notifying the party that caused the event.

5.4.8 Vulnerability Assessment

Cybertrust performs an annual risk assessment once a year that identifies and assess reasonably foreseeable internal and external threats that could result in unauthorized access, disclosure, misuse, alteration, or destruction of the Certification Authorities (The OCSP servers of the Certification Authorities including.). Cybertrust also routinely assesses the sufficiency of procedures, information systems, technology, and other arrangements that Cybertrust has in place to control such risks. Cybertrust's Internal Auditors review the security audit data checks. Cybertrust's audit log monitoring tools alert the appropriate personnel of any events, such as repeated failed actions, requests for privileged information, attempted access of system files and unauthenticated responses.

5.5 Records Archival

5.5.1 Records to be Archived

The Certification Authorities shall archive the following information in addition to the monitoring logs prescribed in "5.4.1 Types of Events to be Recorded" of this CPS:

- (i) Certification Authority Certificate;
- (ii) Subscriber Certificate;
- (iii) CRL;
- (iv) internal audit report;
- (v) external audit report;
- (vi) application forms and data; and
- (vii) this CPS.

5.5.2 Record Archival Period

The Certification Authorities shall archive the records prescribed in "5.5.1 Records to be Archived" of this CPS "5.5.1 Records to be Archived" for at least 7 years beyond the effective period of the relevant certificate or during the operation period of the Certification Authorities, whichever comes first.

When records are no longer required, the Certification Authorities shall dispose such records based on the provisions of "5.1.8 Waste Disposal" of this CPS.

5.5.3 Record Protection

Records shall be protected based on the same procedures as "5.4.4 Audit Log Protection" of this CPS.

5.5.4 Record Backup Procedures

Records shall be backed up based on the same procedures as "5.4.5 Audit Log Backup Procedures" of this CPS.

5.5.5 Time-stamping

The Certification Authorities shall record the drafting date or processing date on forms and the like. If the date alone will lack authenticity as a record, the time should also be recorded. Record the issued date and time for certificates. The Certification Authorities system shall undergo necessary measures for recording the accurate date and time of the issued certificate and monitoring logs.

5.5.6 Record Collecting System

Certificates shall automatically be collected based on the function of the Certification Authority system. Other paper mediums shall be collected by the Certification Authority Staff.

5.5.7 Record Acquisition and Verification Procedures

The Certification Authorities shall limit persons authorized to acquire and peruse records to the member of CTJ PA, the Certification Authority Staff, the auditor and persons authorized by the Certification Authority Supervisor. Verification regarding the legibility of records shall be implemented as needed.

5.6 Key Change Over of Certification Authority

Not applicable.

The Subordinate CA will renew the key pair of the Subordinate CA by the new application to this service so that the validity of the certificates of the Subordinate CA will not expire.

5.7 Compromise and Disaster Recovery

5.7.1 Compromise and Disaster Recovery Procedures

5.7.1.1 In the event of Compromise of the Subordinate CA

When the private key of the Subordinate CA is compromised in this service, Cybertrust shall execute the following, and simultaneously notify the fact of such compromise to subscribers and relying parties:

- (i) discontinuation of certification operations using the compromised private key;
- (ii) revocation of all certificates;
- (iii) investigation of the cause of compromise;
- (iv) formulation of proposed remedial measures and evaluation/approval thereof by CTJ PA;
- (v) execution of remedial measures;
- (vi) assessment on appropriateness of resuming business operations;
- (vii) accepting new application for this service, generation of new key pairs and providing the Subordinate CA;
- (viii) resumption of certification operations (including notification to subscribers and relying parties); and
- (ix) reissuance of Subscriber Certificates

When the Subordinate CA suffers from a disaster, the Subordinate CA shall perform recovery operations using backup hardware, software and data based on the business continuation plan prescribed in "Business Continuity upon Disasters" of this CPS, exert efforts to resume the certification operations, and publish the fact of such resumption to the subscribers and relying parties when the certification operations are resumed.

5.7.1.2 In the event of Compromise of Root CA

When Cybertrust learns that the private key of the Root CA has been compromised, Cybertrust shall execute the following, and simultaneously notify the fact of such compromise to the browser vendor that has registered the Root CA Certificate, and publish the same in the repositories:

- (i) discontinuation of certification operations using the compromised private key;
- (ii) revocation of all certificates of the Subordinate CA that were issued after the launch of the Root CA; and
- (iii) examination, determination and implementation of measures (including, but not limited to, dealing with the Subordinate CA, investigation of the cause of compromise, corrective action, and method of resuming services).

When the Root CA suffers from a disaster, the Root CA shall perform recovery operations of backup key information and data based on the business continuation plan prescribed in "5.7.4 Business Continuity upon Disasters" of this CPS, exert efforts to resume the certification operations, and publish the fact of such resumption in the repositories when the certification operations are resumed.

5.7.2 Procedures upon System Resource Failure

When hardware, software or data is destroyed, the Certification Authorities shall recover the system through maintenance and by using backup data and the like, and continue performing the certification operations.

5.7.3 Procedures upon Compromise of Subscriber Private Key

In the event the private key that is being managed under the subscriber's own responsibility is compromised, or suspected of being compromised, the subscriber must take the revocation procedures of the Subscriber Certificate based on the procedures prescribed in "4.9 Certificate Revocation and Suspension" of this CPS.

The Subordinate CA revokes a Subscriber Certificate based on "4.9 Revocation Request Procedures" of this CPS.

5.7.4 Business Continuity upon Disasters

The Root CA shall separately set forth a business continuation plan regarding the recovery measures for recovering from disasters, and business continuity. The business continuation plan defines the operating procedures of recovery and resumption of all or a part (revocation processing) of the operations of the Root CA by using data and the like stored in the Facility.

With regard to the recovery time from disasters, the step-by-step recovery target is set forth in the business continuation plan based on investigations of the disaster situation.

With regard to the business continuation plan for the Subordinate CA, the plan for Root CA shall apply correspondingly.

5.8 Termination of Certification Authority Operations

When the Root CA is to terminate the operations of the Root CA, the Root CA shall publish information to such effect in advance on Cybertrust's website.

The Subordinate CA shall deem that the operation of the Subordinate CA has been terminated when the Subordinate CA terminates the use of this service.

The information of subscribers held by the Subordinate CA shall be abolished or provided to the transferee of business operations.

6. Technical Security Controls

6.1 Key Pair Generation and Installation

6.1.1 Key Pair Generation

The key pair used in the Root CA was acquired by Cybertrust after JCSI terminated the provision of its service using the root certificate in 2014 as described in "1.1 Overview" of this CPS. In acquiring the key pair, Cybertrust prepared a private key cryptographic module ("HSM") that satisfies the standards of FIPS PUB 140-2 Level 3 for managing the key pair of the Root CA, and transferred the key pair to Cybertrust's HSM, via the secrecy distribution method, from the HSM of the same standards that were being used by JCSI to control the key pair.

The key pair of the Root CA shall be transferred in the presence of the auditor set forth in "8.2 Auditor Requirements" and "8.3 Relation of Auditor and Auditee" of this CPS or, when the auditor is not available, by presenting to the auditor the transfer records and the recording of the key confirmation procedures so as to ensure that the transfer of the key pair of the Root CA was performed according to predetermined procedures.

The key pair of an OCSP server certificate and the Subordinate CA Certificate shall be generated by multiple Issuing Authority System Administrators based on Certification Authority Supervisor's instructions under the control of the Issuing Authority Manager.

In generating the key pair of the Subordinate CA, the HSM that satisfies the standards of FIPS PUB 140-2 Level 4 shall be used. In generating the key pair of the OCSP server, the HSM that satisfies the standards of FIPS PUB 140-2 Level 3 shall be used.

The key pair of the Subordinate CA shall be generated in the presence of the auditor set forth in "8.2 Auditor Requirements" and "8.3 Relation of Auditor and Auditee" of this CPS or, when the auditor is not available, by presenting to the auditor the recording of the generation procedures so as to ensure that the generation of the key pair of the Subordinate CA was performed according to predetermined procedures.

6.1.2 Delivery of Subscriber Private Key

The Subordinate CA does not deliver a subscriber's private key. A subscriber's private key shall be generated independently by the subscriber.

6.1.3 Delivery of Subscriber Public Key to Certification Authority

A subscriber shall include the public key in the data for requesting the issuance of a Certificate, and then deliver the same to the Subordinate CA via email.

6.1.4 Delivery of Certification Authority Public Key to Relying Parties

The Subordinate CA does not deliver the public key of the Subordinate CA to relying parties.

The certificates of the Root CA including the public key of the Root CA is published in the repositories.

6.1.5 Key Length

The key signature algorithm and key length of the Root CA certificate shall be as follows.

Certification Authority Name	Signature Algorithm	Key Length
SecureSign RootCA11	SHA1 with RSA	2048 bit

The key signature algorithm and key length of an OCSP server certificate shall be as follows.

OCSP Server Certificate	Signature Algorithm	Key Length
OCSP server certificate issued by SecureSign RootCA11 or the Subordinate CA	SHA2 with RSA	2048 bit

The key signature algorithm and key length of the Subordinate CA Certificate shall be as follows.

Subordinate CA Certificate	Signature Algorithm	Key Length
The Subordinate CA Certificate issued by SecureSign RootCA11	SHA2 with RSA	2048 bit

The key signature algorithm and key length of the Subscriber Certificate shall be as follows.

Subscriber Certificate	Signature Algorithm	Key Length
Subscriber certificate issued by the Subordinate CA	SHA2 with RSA	2048 bit

6.1.6 Generation and Check of Public Key Parameter

The Certification Authorities shall confirm that the value of the public exponent is an odd number equal to 3 or more. And the public exponent shall be in the range between $2^{16}+1$ and $2^{256}-1$. The modulus shall also have the following characteristics: an odd number, not the power of a prime, and have no factors smaller than 752.

6.1.7 Key Usage

The key usage of the Root CA Certificate shall be Certificate Signing, CRL Signing.

The key usage of the Subordinate CA certificate shall be Certificate Signing, CRL Signing.

The key usage of Subscriber Certificate shall be Digital Signature, Key Encipherment.

The key usage of an OCSP server certificate shall be Digital Signature.

6.2 Private Key Protection and Cryptographic Module Engineering Controls

6.2.1 Cryptographic Module Standards and Controls

The cryptographic module for controlling the key pair of the Root CA shall be the HSM that satisfies the FIPS PUB 140-2 Level 3 standard. The HSM shall be controlled by the Issuing Authority.

The cryptographic module for controlling the key pair of the Subordinate CA shall be the HSM that satisfies the FIPS PUB 140-2 Level 4 standard. The HSM shall be controlled by the Issuing Authority.

The key pair of an OCSP server certificate shall be controlled by the HSM that satisfies the FIPS 140-2 Level 3 standard. The OCSP server shall be controlled by the Issuing Authority.

6.2.2 Private Key Controls by Multiple Persons

The private key used by the Certification Authorities and the OCSP servers shall at all-time be controlled by multiple Issuing Authority System Administrators.

6.2.3 Private Key Escrow

The Certification Authorities do not deposit the private key used by the Certification Authorities and the OSCP servers, or deposit the private key of subscribers.

6.2.4 Private Key Backup

The Issuing Authority System Administrator shall back up the private key of the Certification Authorities. The private key backed up from the HSM shall be encrypted and then divided into multiple pieces, and safely stored in a lockable safe.

The private key to be used in an OSCP server is backed up and archived by the Issuing Authority System Administrator in an encrypted state as the backup of the system.

6.2.5 Private Key Archive

The Certification Authorities shall not archive the private key used by the Certification Authorities and the OSCP servers.

6.2.6 Private Key Transfer

The Root CA shall not generate the Private Key on behalf of the Subordinate CA.

The Certification Authority transfers a copy of the private key used by the Certification Authority to the backup site based on a safe method. When it is necessary to restore the private key of the Certification Authority due to a failure of the HSM or other reasons, the Issuing Authority System Administrator shall restore the private key using the backup stored in the main site or the backup site.

When the recovery of the private key of an OSCP server is required, the Issuing Authority System Administrator shall perform such recovery by using the system backup archived in the main site; provided, however, that, based on the approval of the Certification Authority Supervisor, there may be cases where the corresponding certificate is revoked, and a private key is newly generated.

6.2.7 Private Key Storage in Cryptographic Module

The private key of the Root CA and the OSCP servers shall be stored in the HSM that satisfies the standards of FIPS PUB 140-2 Level 3.

The private key of the Subordinate CA shall be stored in the HSM that satisfies the standards of FIPS PUB 140-2 Level 4.

6.2.8 Private Key Activation

The private key used by the Certification Authorities and the OSCP servers shall be activated by multiple Issuing Authority System Administrators based procedures to be separately prescribed based on the approval of the Issuing Authority Manager. The activation operation shall be recorded.

6.2.9 Private Key Deactivation

The private key used by the Certification Authorities and the OSCP servers shall be deactivated by multiple Issuing Authority System Administrators based procedures to be separately prescribed based on the approval of the Issuing Authority Manager. The deactivation operation shall be recorded.

6.2.10 Private Key Destruction

The private key used by the Certification Authority and the OSCP server shall be destroyed by multiple Issuing Authority System Administrators based procedures to be separately prescribed based on the approval of the Issuing Authority Manager and according to instructions of the Certification Authority Supervisor. Simultaneously, the private key of the Certification Authority that was backed up pursuant to "6.2.4 Private Key Backup" of this CPS shall also be destroyed based on the same procedures. The destruction operation shall be recorded.

6.2.11 Cryptographic Module Assessment

The Certification Authorities shall use the HSM that satisfies the standards set forth in "6.2.1 Cryptographic Module Standards and Controls" of this CPS.

6.3 Other Aspects of Key Pair Management

6.3.1 Storage of Public Key

Storage of the public key shall be carried out by storing the certificate including that public key.

6.3.2 Certificate Operational Periods and Key Pair Usage Periods

The validity period of the key pair of the Root CA shall be as follows.

Key Pair	Validity Period
Key Pair of the Root CA	April 8, 2029

The validity period of the key pair of the Subordinate CA shall be as follows.

Key Pair	Validity Period
Key Pair of the Subordinate CA	No later than April 8, 2029

The validity period of the OCSP server certificate shall be as follows.

Certificate	Validity Period
OCSP Server Certificate	Within 25 months

The validity period of the Subscriber Certificate shall be as follows.

Certificate	Validity Period
Subscriber Certificate	As specified in BR 6.3.2 (Within 825 days)

6.4 Activation Data

6.4.1 Creation and Setting of Activation Data

The activation data used by the Certification Authorities shall be created and set upon giving consideration so that it cannot be easily speculated.

6.4.2 Activation Data Protection and Controls

The activation data used in the Certification Authorities shall be stored in a lockable safe in a room that is subject to entrance/exit control based on the provisions of "5.1.2 Physical Access" of this CPS.

6.4.3 Other Aspects of Activation Data

Not Applicable.

6.5 Computer Security Controls

6.5.1 Technical Requirements of Computer Security

The Certification Authority system shall perform the following as security measures:

- (i) authentication of authority of the operator;
- (ii) identification and authentication of the operator;

- (iii) acquisition of operation logs for important system operations;
- (iv) setup of appropriate passwords; and
- (v) backup and recovery.

6.5.2 Computer Security Assessment

The Certification Authorities shall implement, in advance, installation assessment of hardware and software to be installed by the Certification Authorities. The Certification Authorities shall also continuously collect information and perform evaluations regarding the security vulnerability in the system to be used, and take necessary measures based on the evaluation results.

6.6 Life Cycle Security Controls

6.6.1 System Development Controls

The construction and change of the Certification Authority system shall be performed based on provisions to be separately set forth under the control of the development supervisor appointed internally by Cybertrust. When the development supervisor deems necessary, necessary and sufficient verification shall be carried out in a testing environment to confirm that there are no security-related problems.

6.6.2 Security Management Controls

The Certification Authority system shall undergo necessary settings in order to ensure sufficient security. In addition to implementing entrance/exit control and access authorization control according to the security level, the Certification Authorities shall continuously collect information and perform evaluations regarding the security vulnerability, and take necessary measures based on the evaluation results.

6.6.3 Life Cycle Security Controls

The Certification Authorities shall appoint a supervisor in the respective processes of development, operation, change, and disposal of the Certification Authority system, formulate and evaluate the work plan or procedures, and conduct testing as needed. The respective operations shall be recorded.

6.7 Network Security Controls

The Root CA system shall not be connected to a network, and shall be operated offline.

The Subordinate CA system, OCSP server system and external systems such as the internet shall be connected via a firewall or the like, and be monitored by an intrusion detection system.

6.8 Time-stamping

According to "5.5.5 Time-stamping" of this CPS.

7. Certificate, CRL and OSCP Profiles

7.1 Certificate Profile

7.1.1 Version No.

Matters are described in Appendix B.

7.1.2 Certificate Extensions

Matters regarding the certificates of the Certification Authority are described in Appendix B.

7.1.3 Algorithm Object Identifier

Matters are described in Appendix B.

7.1.4 Name Format

Matters are described in Appendix B.

Note that underscore characters ('_') must not be present in dNSName entries.

Subject attributes must not contain only metadata such as '.' (i.e. period), '-' (i.e. hyphen), and ' ' (i.e. space) characters, and/or any other indication that the value is absent, incomplete, or not applicable.

Other attributes may be present within the subject field. If present, other attributes must contain information that has been verified by the Certification Authorities.

7.1.5 Name Restrictions

The Subordinate CA includes name constraint in the nameConstraints field in the Subordinate CA Certificate.

7.1.6 Certificate Policy Object Identifier

The policy object identifier of the Subscriber Certificate shall be as prescribed in "1.2 Document Name and Identification" of this CPS.

In addition, it includes {joint-iso-itu-t(2) international-organizations(23) ca-browser-forum(140) certificate-policies(1) baseline-requirements(2) organization-validated(2)} - 2.23.140.1.2.2 defined by CABF.

The policy object identifier of the Subordinate CA Certificate shall be anyPolicy: 2.5.29.32.0.

The policy object identifier of the Root CA Certificate shall be as prescribed in "1.2 Document Name and Identification" of this CPS.

7.1.7 Use of Policy Constraint Extensions

Not applicable.

7.1.8 Construction and Meaning of Policy Modifier

Matters are described in Appendix B.

7.1.9 Processing Method of Certificate Policy Extensions

Not applicable.

7.2 CRL Profile

7.2.1 Version No.

Matters are set forth in Appendix B.

7.2.2 CRL, CRL Entry Extensions

Matters are set forth in Appendix B.

7.3 OCSP Profile

7.3.1 Version No.

Matters are set forth in Appendix B.

7.3.2 OCSP Extensions

Matters are set forth in Appendix B.

8. Compliance Audit and Other Assessment

8.1 Audit Frequency and Requirements

The Root CA verifies the Trust Service Principles and Criteria for Certification Authorities and the WebTrust Principles and Criteria for Certification Authorities – SSL Baseline with Network Security once a year, or performing a visiting audit at the timing deemed necessary by the auditor "8.2 Auditor Requirements" of this CPS.

The Subordinate CA, which is the Technically Constrained Subordinate CA, conduct an audit set forth in the BR 8.7 in accordance with the BR 8.1.

8.2 Auditor Requirements

A qualified outside auditor shall verify the Trust Service Principles and Criteria for Certification Authorities and the WebTrust Principles and Criteria for Certification Authorities – SSL Baseline with Network Security.

8.3 Relation of Auditor and Auditee

The auditor shall be, as a general rule, a party that is independent from the operations of the Certification Authorities and capable of maintaining neutrality.

8.4 Scope of Audit

The scope of audit for the Root CA shall be the scope set forth in the Trust Service Principles and Criteria for Certification Authorities and the WebTrust Principles and Criteria for Certification Authorities – SSL Baseline with Network Security.

The scope of audit for the Subordinate CA shall be in accordance with the BR 8.7.

8.5 Measures against Identified Matters

Identified matters that are discovered in the verification shall be reported to the CTJ PA, the Certification Authority Supervisor, the Issuing Authority Manager and the Registration Authority Manager. When the auditor, the CTJ PA, the Certification Authority Supervisor, the Issuing Authority Manager or the Registration Authority Manager determines that corrective action is required, corrective action shall be taken under the control of the Issuing Authority Manager or the Registration Authority Manager.

8.6 Disclosure of Audit Results

Verification results of the Trust Service Principles and Criteria for Certification Authorities and the WebTrust Principles and Criteria for Certification Authorities – SSL Baseline with Network Security shall be published according to the provisions of the respective guidelines.

8.7 SELF-AUDITS

During the period in which the Subordinate CA issues Subscriber Certificates, the Subordinate CA shall monitor adherence to its CPS and BR and strictly control its service quality by performing self-audits on at least a quarterly basis against a randomly selected sample of the greater of one certificate or at least three percent of the Subscriber Certificates issued by it during the period commencing immediately after the previous self-audit sample was taken.

9. Other Business and Legal Matters

9.1 Fees

The fees for this service shall be notified so that a subscriber can properly verify the same.

9.2 Financial Responsibility

Cybertrust shall maintain a sufficient financial foundation that is required for observing the subject matter set forth in this CPS and operating the Certification Authorities. Cybertrust shall also take out appropriate insurance for covering its indemnity liability.

9.3 Confidentiality of Business Information

9.3.1 Scope of Confidential Information

The Certification Authorities shall handle the following information as confidential information (the "Confidential Information"):

- (i) application information;
- (ii) information set forth in "9.4.2 Information Handled as Personal Information" of this CPS;
- (iii) inquiry information received from a third party (including relying parties); and
- (iv) information relating to the security of the Certification Authorities.

9.3.2 Information Outside Scope of Confidential Information

Of the information held by the Certification Authorities, the following information shall be excluded from the scope of Confidential Information:

- (i) information set forth as in "2.2 Information to be Published" of this CPS as information to be published;
- (ii) the Subscriber Certificate, The Subordinate CA Certificate and the Root CA Certificate;
- (iii) information which became public knowledge due to reasons other than the negligence on the part of the Certification Authorities;
- (iv) information which became public knowledge without any restriction of confidentiality from a party other than the Certification Authorities; and
- (v) information for which the subscriber and/or relying party agreed in advance to the effect of being disclosed or provided to a third party.

9.3.3 Responsibility of Protecting Confidential Information

The Certification Authorities shall take measures for preventing the divulgence of the Confidential Information. The Certification Authorities shall not use the Confidential Information for any purpose other than for performing its operations; provided, however, that, when disclosure of the Confidential Information is demanded in the course of judicial, administrative or other legal proceedings; or when the Confidential Information is to be disclosed to a party such as a financial advisor or a potential acquirer/acquire that executed a confidentiality agreement with Cybertrust in relation to an acquisition/merger and/or a party such as an attorney, certified public accountant, tax attorney or the like that legally bears the confidentiality obligation, or when Cybertrust obtains the prior approval of the party disclosing the Confidential Information, Cybertrust may disclose the Confidential Information to the party requesting disclosure of such Confidential Information. In the foregoing case, the party receiving the disclosure of the requested Confidential Information must not disclose or divulge such information to any third party regardless of the method thereof.

The handling of protection of personal information shall be set forth in "9.4 Protection of Personal Information" of this CPS.

9.4 Protection of Personal Information

9.4.1 Privacy Policy

Handling of personal information held by the Certification Authorities shall be set forth in the Privacy Policy that is published on Cybertrust's website (<https://www.cybertrust.co.jp/corporate/privacy-policy.html>).

9.4.2 Information Handled as Personal Information

The Certification Authorities shall handle, as personal information, any information that is included in inquiries or the like capable of identifying a specific individual.

9.4.3 Information not Deemed Personal Information

The Certification Authorities shall not deem, as personal information, any information other than the information set forth in "9.4.2 Information Handled as Personal Information" of this CPS.

9.4.4 Responsibility of Protecting Personal Information

The responsibility of protecting the personal information held by the Certification Authorities shall be as set forth in "9.4.1 Privacy Policy" of this CPS.

9.4.5 Notification to and Consent from Individuals on Use of Personal Information

Based on a subscriber's issuance application or revocation request, it shall be deemed that the Certification Authorities has obtained the consent of the subscriber with regard to the Certification Authorities using the personal information of that subscriber for performing its certificate issuance/revocation operations that are scheduled in this CPS and the Certification Authorities conducting an audit.

Moreover, the Certification Authorities shall not use the acquired personal information for any purpose other than for performing the certification operations; save for the case set forth in "9.4.6 Disclosure based on Judicial or Administrative Procedures" of this CPS.

9.4.6 Disclosure based on Judicial or Administrative Procedures

When disclosure of personal information handled by the Certification Authorities is demanded in the course of judicial, administrative or other legal proceedings, Cybertrust may disclose such personal information.

9.4.7 Other Cases of Information Disclosure

When the Certification Authorities are to outsource a part of its operations, there may be cases where the Certification Authorities need to disclose the Confidential Information to the outsourcee. In the foregoing case, the Certification Authorities shall include a provision in the service contract which imposes a confidentiality obligation on the outsourcee for maintaining the confidentiality of the Confidential Information.

9.5 Intellectual Property Rights

Unless separately agreed herein, all intellectual property rights pertaining to the following information related to this service shall belong to Cybertrust related to this service:

- (i) this CPS;
- (ii) public key and private key of the Certification Authorities; and
- (iii) certificates issued by the Certification Authorities and revocation information on and after the launch date.

9.6 Representations and Warranties

The representations and warranties of the Issuing Authority, the Registration Authority and the Relying Parties are prescribed below. Excluding the representations and warranties of the Issuing Authority, the Registration Authority and the Relying Parties that are expressly prescribed in "9.6 Representations and Warranties" of this CPS, the respective parties mutually confirm that they will not make any express or implied representation or warranty.

9.6.1 Representations and Warranties of Issuing Authority

Issuing Authority represents and warrants that it bears the following obligations upon performing operations as the Issuing Authority:

- (i) to safely control the Certification Authorities private key;
- (ii) to perform accurate certificate issuance and revocation based on the application from the Registration Authority;
- (iii) to provide revocation information by the CRL and the OCSP server;
- (iv) to monitor and operate the Certification Authorities system; and
- (v) to maintain and control the repositories.

9.6.2 Representations and Warranties of Registration Authority

Registration Authority represents and warrants that it bears the following obligations upon performing operations as the Registration Authority:

- (i) perform screening of subscribers based on this CPS;
- (ii) properly handle certificate issuance applications and revocation requests to the Issuing Authority; and
- (iii) accept inquiries ("1.5.2 Contact Point" of this CPS).

9.6.3 Representations and Warranties of Subscribers

Subscriber represents and warrants that it bears the following obligations:

- (i) provide true and accurate information upon applying for the issuance of a Subscriber Certificate;
- (ii) comply with the usage of the Subscriber Certificate;
- (iii) refrain from using the Subscriber Certificate in websites and emails that are contrary to public order and morals;
- (iv) refrain from requesting and using a Subscriber Certificate in conflict with NameConstraints in the Subordinate CA Certificate;
- (v) refrain from including the organization unit(OU) in Subscriber Certificate;
- (vi) refrain from installing a Subscriber Certificate in a server and using the Subscriber Certificate until the accuracy of the information included in the certificate is confirmed;
- (vii) strictly manage the private key and password to ensure the confidentiality and safety thereof;
- (viii) install a Subscriber Certificate only in a server that is accessible by the FQDN included in the Subscriber Certificate, and use the Subscriber Certificate only for the business acknowledged by Subscriber according to the subscriber agreement;
- (ix) in the occurrence of an event set forth in 4.9.1.1 of this CPS, promptly submit an application for the revocation of the Subscriber Certificate;
- (x) upon determining that the private key has been compromised or there is a possibility thereof, promptly submit an application for the revocation of the Subscriber Certificate;
- (xi) refrain from using an expired Subscriber Certificate or a revoked Subscriber Certificate; and
- (xii) observe applicable laws and regulations.

9.6.4 Representations and Warranties of Relying Parties

The relying parties represent and warrant that they bear the following obligations:

- (i) to confirm whether the certificate is used for the for the usage set forth in "1.4.2 Appropriate Certificate Uses" of this CPS;
- (ii) to confirm the effective period and entries of the Subordinate CA;
- (iii) to verify the digital signature and confirm the issuer of the Certification Authority certificate;
- (iv) to confirm whether the certificate has been revoked based on CRL or the OCSP server; and
- (v) to bear legal liability for situations arising from the default of obligations prescribed in this paragraph.

9.6.5 Representations and Warranties of Other Relevant Parties

Not applicable.

9.7 Disclaimers of Warranties

The Certification Authorities shall not be liable for any default based on this CPS regarding damages excluding direct damages arising in relation to the warranties set forth in "9.6.1 Representations and Warranties of Issuing Authority" and "9.6.2 Representations and Warranties of Registration Authority" of this CPS.

The Certification Authorities shall not be liable in any way for the consequences resulting from a relying party trusting the Certification Authority certificate based on one's own judgment.

9.8 Limitations of Liability

Cybertrust shall not be liable in any way in the following cases in relation to the subject matter of "9.6.1 Representations and Warranties of Issuing Authority" and "9.6.2 Representations and Warranties of Registration Authority" of this CPS:

- (i) any damage that arises regardless of the Certification Authorities observing this CPS and legal regulations;
- (ii) any damage that arises due to fraud, unauthorized use or negligence that is not attributable to Cybertrust;
- (iii) damage that arises as a result of the relying parties neglecting to perform their respective obligations prescribed in "9.6 Representations and Warranties" of this CPS;
- (iv) damage that arises as a result of the key pair of the certificate issued by the Certification Authorities being divulged or compromised due to acts of a third party other than Cybertrust;
- (v) damage that arises as a result of the certificate infringing upon the copyright, trade secret or any other intellectual property right of subscribers, a relying party or a third party; or
- (vi) damage caused by the weakening of the cryptographic strength resulting from technological advances such as improvement in the encryption algorithm decoding technology, or by any other vulnerability of the encryption algorithm.

The total amount of damages to be borne by Cybertrust against subscribers and relying parties or other third parties with regard to any and all damages arising in relation to the application, approval, trust or any other use of this service and/or the certificates shall not exceed 10,000,000 yen under no circumstances whatsoever.

This upper cap shall be applied to each certificate regardless of the number of digital signatures, number of transactions, or number of damages pertaining to the respective certificates, and shall be allocated in order from the claim that is made first.

Among the damages arising from any default or breach of this CPS, the Certification Authorities shall not be liable for any data loss, indirect damages including lost profits, consequential damages and punitive damages to the extent permitted under the governing law set forth in "9.14 Governing Law" of this CPS.

9.9 Indemnities

At the time that a relying party receives or uses the Certification Authority certificate, that relying party shall become liable for compensating any damage suffered by Cybertrust due to claims made by a third party against Cybertrust or lawsuits or other legal measures initiated or taken by a third party against Cybertrust resulting from any of the following acts conducted by the relying party, as well as become responsible for taking measures so that Cybertrust will not suffer any more damage:

- (i) unauthorized use, falsification, or misrepresentation during the use of the Certification Authority certificate;
- (ii) breach of this CPS. breach of this CPS or the subscriber agreement; or
- (iii) neglect by a subscriber to preserve the private key.

The Certification Authority is not the relying party's agent, trustee or any other representative.

9.10 Term of Document and Termination

9.10.1 Term of Document

This CPS shall come into effect when approved by the CTJ PA. This CPS will not be invalidated before the time set forth in "9.10.2 Termination" of this CPS.

9.10.2 Termination

This CPS shall become invalid at the time that the Root CA terminates its operations, excluding the cases prescribed in "9.10.3 Influence of Termination and Surviving Provisions" of this CPS.

9.10.3 Influence of Termination and Surviving Provisions

The provisions of 9.3, 9.4, 9.5, 9.6, 9.7, 9.8, 9.9, 9.10.2, 9.10.3, 9.13, 9.14, 9.15, and 9.16 of this CPS shall continue to remain in force even after the termination of this CPS.

9.11 Individual Notices and Communications with Participants

When Cybertrust is to notify subscribers individually, such notice shall deem to have been made when a written notice is hand-delivered, delivered via registered mail with verification of receipt, or sent via email. Moreover, notices from subscribers to Cybertrust shall all be made in writing, and such notices shall be deemed to have arrived when such notices are sent and received by Cybertrust.

9.12 Amendments

9.12.1 Amendment Procedures

The Root CA shall amend this CPS on instructions from the CTJ PA at least once a year to meet the various requirements, also increment its version number and add a dated changelog entry. The CTJ PA shall approve the amendment after obtaining the evaluation of the Certification Authority Staff or the evaluation of outside professionals such as attorneys or other experts as needed.

9.12.2 Notification Method and Period

After the CTJ PA approves the amendment of this CPS, the Root CA shall take measures to post the CPS before amendment and the CPS after amendment for a given period on the website so that the relying parties can confirm the amended contents. The amended CPS shall come into force at the time that is set forth by the CTJ PA unless the withdrawal of the amended CPS is publicly announced by Cybertrust.

9.12.3 Change of Object Identifier

CTJ PA is responsible to decide if the OID updates are required correspondingly to this CPS change.

9.13 Dispute Resolution Procedures

Any and all disputes arising in relation to this CPS or the certificates issued by the Certification Authorities shall be submitted to the Tokyo District Court as the competent court of agreed jurisdiction for the first instance. With regard to matters that are not set forth in this CPS or when doubts arise with regard to this CPS, the parties shall consult in good faith to resolve such matters.

9.14 Governing Law

This CPS is construed in accordance with the laws of Japan, and the laws of Japan shall apply any dispute pertaining to the certification operations based on this CPS.

9.15 Compliance with Applicable Law

This CPS is subject to all applicable laws and regulations.

9.16 Miscellaneous Provisions

9.16.1 Entire Agreement

Unless separately specified herein, the matters agreed in this CPS supersede all other agreements unless this CPS is amended or terminated.

9.16.2 Assignment of Rights

When Cybertrust is to assign this service to a third party, this CPS and the liabilities and other obligations set forth in this CPS may also be assigned to such third party.

9.16.3 Severability

Even if any provision of this CPS is found to be invalid for one reason or another, the remaining provisions shall continue to remain in force.

9.16.4 Enforceability

Cybertrust may seek indemnification and attorneys' fees from a party for damages, losses, and expenses related to that party's conduct. Cybertrust's failure to enforce a provision of this CPS does not waive Cybertrust's right to enforce the same provision later or right to enforce any other provision of this CPS. To be effective, waivers must be in writing and signed by Cybertrust.

9.16.5 Force Majeure

In the event the performance of a part or all of the obligations under this CPS is delayed due to calamities, court orders, labour disputes, or other reasons that are not attributable to Cybertrust, Cybertrust shall be exempted from the performance of its obligations under this CPS during the delay period, and shall not be liable in any way against a third party that trusted or used the certificate.

9.17 Other Provisions

Not Applicable.

Appendix A: List of Definitions

Term	Definition
Archive	As used herein, the term "archive" refers to the process of storing expired certificates for a predetermined period.
Cryptographic Module	Software, hardware, or a device configured from the combination of such software and hardware that is used for ensuring security in the generation, storage and use of private keys.
Suspension	Measure for temporarily invalidating a certificate during the effective period of that certificate.
Key Pair	A public key and a private key in public key cryptography. The two keys are unique in that one key cannot be derived from another key.
Key Length	A bit number that represents the key length which is also a factor in deciding the cryptographic strength.
Activation	To cause a system or device to be a usable state. Activation requires activation data, and specifically includes a PIN and pass phrase.
Compromise	A state where the confidentiality or completeness of information that is incidental to the private key and the private key is lost.
Public Key	One key of the key pair in public key cryptography that is notified to and used by the other party (communication partner, etc.).
Revocation	Measure for invalidating a certificate even during the effective period of that certificate.
Certificate Revocation List	Abbreviated as "CRL" in this CPS. CRL is a list of revoked certificates. The Certification Authority publishes CRL so that the subscribers and relying parties can confirm the validity of certificates.
Certification Operations	Series of operations that are performed during the life cycle controls of certificates. Including, but not limited to, operations of accepting issuance/revocation applications, screening operations, issuance/revocation/discarding operations, operations of responding to inquiries, billing operations, and system maintenance and management operations of Certification Authorities.
Backup Site	A facility that is separate from the main site for storing important assets of the Certification Authorities required for certificate issuance and revocation to ensure business continuity during disasters, etc.
Private Key	One key of the key pair in public key cryptography that is kept private from others.
Policy Authority (CTJ PA)	The committee set forth by Cybertrust that supervise the Certification Authority and reviews/approves the policy with independent from the Certification Authority.
Main Site	A facility equipped with assets of the Certification Authorities required for certificate issuance and revocation.
Escrow	As used herein, the term "escrow" refers to the processing of registering and storing a private key or a public key with a third party.

Repository	A website or system for posting public information such as this CPS and CRL.
Baseline Requirements	“Baseline Requirements for the Issuance and Management of Publicly-Trusted Certificates”. Requirements for issuing publicly-trusted certificates which are formulated by the CA/Browser Forum and the latest version shall be adopted in this CPS.
CAA contactemail Property	The CAA contactemail property takes an email address as its parameter. The entire parameter value must be a valid email address as defined in RFC 6532 section 3.2, with no additional padding or structure, or it cannot be used. SYNTAX: contactemail <rfc6532emailaddress> The following is an example where the holder of the domain specified the contact property using an email address. \$ORIGIN example.com. CAA 0 contactemail "domainowner@example.com" The contactemail property may be critical, if the domain owner does not want CAs who do not understand it to issue certificates for the domain.
CA/Browser Forum	A voluntary group of certification authorities, vendors of Internet browser software, and suppliers of other applications that use X.509 v.3 digital certificates for SSL/TLS and code signing. It conducts activities such as adaptation of EV Guidelines and Baseline Requirements. The URL is https://www.cabforum.org .
Certification Authority Authorization Resource Record (CAA Record)	One of the DNS records defined in RFC6844 which aims to clarify the certification authority to issue the server certificate to a domain name and prevent the issuance of unintended certificates.
Distinguished Name	An identifier set forth in the X.500 recommendation formulated by ITU-T. Configured from attribute information such as a common name, organization name, organizational unit name, and country name.
DNS TXT Record Email Contact	The DNS TXT record must be placed on the "_validation-contactemail" subdomain of the domain being validated. The entire RDATA value of this TXT record must be a valid email address as defined in RFC 6532 section 3.2, with no additional padding or structure, or it cannot be used.
DNS TXT Record Phone Contact	The DNS TXT record must be placed on the "_validation-contactphone" subdomain of the domain being validated. The entire RDATA value of this TXT record must be a valid Global Number as defined in RFC 3966 section 5.1.4, or it cannot be used.
FIPS PUB 140-2 Level 3	FIPS PUB 140 (Federal Information Processing Standards Publication 140) is a U.S. federal standard that prescribes the specifications of security requirements in a cryptographic module, and the latest version of this standard is 140-2. With this standard, the security requirements are classified as the levels of 1 (lowest) to 4 (highest).
IETF PKIX Working Group	Internet Engineering Task Force (IETF) is an organization that standardizes technologies used for the internet, and the PKIX Working Group of IETF set forth RFC3647.
IP Address Contact	The person(s) or entity(ies) registered with an IP Address Registration Authority as having the right to control how one or more IP Addresses are used.
IP Address Registration Authority	The Internet Assigned Numbers Authority (IANA) or a Regional Internet Registry (RIPE, APNIC, ARIN, AfriNIC, LACNIC).
ITU-T	Telecommunications Standardization Sector of the International Telecommunication Union.

JCSI SSL/TLS Certificate	The SSL/TLS Certificate issued from JCSI Subordinate CA.
The JCSI Certificate Issuing Service	The Cybertrust's service which provides JCSI Subordinate CA, which is Technically Constrained Subordinate CA, for a Subscriber to get and use a JCSI SSL/TLS Certificates. Cybertrust provides the JCSI Certificate Issuing Service to a Subscriber who gets and use the JCSI SSL/TLS Certificates, however Cybertrust shall not provide this service to any organization other than the Subscriber who has the domain which is registered and restricted as "Technically Constrained".
JCSI Subordinate CA	The Subordinate CA which is the Technically Constrained Subordinate CA and issued under the JCSI Root CA.
OCSP	Abbreviation of "Online Certificate Status Protocol", and is a communication protocol for providing certificate revocation information.
RSA	Public key cryptography developed by Rivest, Shamir, and Adelman.
SHA1/SHA2	A hash function used in digital signatures, etc. A hash function is used for reducing data into a given length based on mathematical operations, and makes it infeasible to calculate the same output value from two different input values. It is also infeasible to inverse the input value from the output value.
SSL/TLS	A protocol for encrypting and sending/receiving information online which was developed by Netscape Communications. TLS is an improvement of SSL 3.0.
Technically Constrained Subordinate CA	The Technically Constrained Subordinate CA Certificate set forth in the Baseline Requirements. That is, the Subordinate CA which uses the Subordinate CA Certificate containing Key Usage Extension and Name Constraint Extension in it to constrain the issuance of Subscriber Certificates.
Trust Service Principles and Criteria for Certification Authorities	Principles related to the operation of Certification Authorities that were formulated by the American Institute of Certified Public Accountants and the Canadian Institute of Chartered Accountants. Formerly called WebTrust Program for Certification Authorities.
WEBTRUST FOR CERTIFICATION AUTHORITIES – SSL BASELINE REQUIREMENTS AUDIT CRITERIA	Requirements for issuing and managing publicly-trusted certificates which were formulated by the American Institute of Certified Public Accountants and the Canadian Institute of Chartered Accountants.
X.500	International standard of distribution directory services to be provided on a network standardized by ITU-T.
X.509	International standard of digital certificates standardized by ITU-T.

Appendix B: Profile of Certificates

SecureSign RootCA11

Root CA Certificate (Effective Period: April 8, 2009 to April 8, 2029)

(Standard Area)

Version		value
Version	version of the encoded certificate type:INTEGER value:2	2 (Ver.3)
Serialnumber		value
CertificateSerialNumber	serial number of certificate type:INTEGER value: unique positive integer	1 (0x01)
Signature		value
AlgorithmIdentifier	the identifier for the cryptographic algorithm used by the CA to sign this certificate Object ID for the cryptographic algorithm (SHA-1) type:OID value:1 2 840 113549 1 1 5	1.2.840.113549.1.1.5
Algorithm		
parameters	Parameters of cryptographic algorithm type:NULL value:	NULL
Issuer		value
CountryName type	Country-name attribute of certificate issuer Object ID for the country name type:OID value:2 5 4 6	2.5.4.6
value	Value of country name type:PrintableString value:JP	JP
OrganizationName type	Organization-name attribute of certificate issuer Object ID for the organization name type:OID value:2 5 4 10	2.5.4.10
value	Value of organization name type:PrintableString value: Japan Certification Services, Inc.	Japan Certification Services, Inc.
CommonName Type	Common-name attribute of certificate issuer Object ID for the common name type:OID value:2 5 4 3	2.5.4.3
value	Value of common name type:PrintableString value: SecureSign RootCA11	SecureSign RootCA11
Validity		value
Validity notBefore	Validity period of certificate the date on which the certificate validity period begins type:UTCTime value:090408045647Z	April 8 th 2009, 04:56:47(GMT)
notAfter	the date on which the certificate validity period ends type:UTCTime value:290408045647Z	April 8 th 2029, 04:56:47(GMT)
Subject		value
CountryName type	Country-name attribute of certificate subject Object ID for the country name type:OID value:2 5 4 6	2.5.4.6
value	Value of country name type:PrintableString value:JP	JP
OrganizationName	Organization-name attribute of certificate subject	

type	Object ID for the organization name type:OID value:2 5 4 10	2.5.4.10
value	Value of organization name type:PrintableString value: Japan Certification Services, Inc.	Japan Certification Services, Inc.
CommonName type	Common-name attribute of certificate subject Object ID for the common name type:OID value:2 5 4 3	2.5.4.3
value	Value of common name type:PrintableString value: SecureSign RootCA11	SecureSign RootCA11
subjectPublicKeyInfo		value
SubjectPublicKeyInfo AlgorithmIdentifier algorithm	Subject's public key information the identifier for the cryptographic algorithm Object ID for the cryptographic algorithm (RSA PUBLIC KEY) type:OID value:1 2 840 113549 1 1 1	1.2.840.113549.1.1.1
parameters	Parameters of cryptographic algorithm type:NULL value:	NULL
subjectPublicKey	Value of public key type: BIT STRING value: public key	2048Bit length of public key

(Expansion Area)

subjectKeyIdentifier (extnId ::= 2 5 29 14, critical ::= FALSE)		value
SubjectKeyIdentifier keyIdentifier	Subject Key Identifier the identifier for the public key type:OctetString value: hash of the value of the BIT STRING subjectPublicKey	5b f8 4d 4f b2 a5 86 d4 3a d2 f1 63 9a a0 be 09 f6 57 b7 de
keyUsage (extnId ::= 2 5 29 15, critical ::= TRUE)		value
KeyUsage	the purpose of the key contained in the certificate. type:BitString value:000001100 (keyCertSign,cRLSign)	000001100
basicConstraints (extnId ::= 2 5 29 19, critical ::= TRUE)		value
BasicConstraints cA	Basic Constraints The flag to determine whether the supplied certificate is associated with a CA or an end entity type:Boolean value: True (associated with the CA)	TRUE

CRL

(Standard Area)

Version		value
Version	version of the encoded certificate/CRL type:INTEGER value:1	1 (Ver.2)
Signature		value
AlgorithmIdentifier	the identifier for the cryptographic algorithm used by the CA to sign this certificate	
Algorithm	Object ID for the cryptographic algorithm (SHA-1) type:OID value:1 2 840 113549 1 1 5	1.2.840.113549.1.1.5
parameters	Parameters of cryptographic algorithm type:NULL value:	NULL
Issuer		value
CountryName type	Country-name attribute of certificate issuer Object ID for the country name type:OID value:2 5 4 6	2.5.4.6
value	Value of country name type:PrintableString value:JP	JP
OrganizationName type	Organization-name attribute of certificate issuer Object ID for the organization name type:OID value:2 5 4 10	2.5.4.10
value	Value of organization name type:PrintableString value: Japan Certification Services, Inc.	Japan Certification Services, Inc.
CommonName type	Common-name attribute of certificate issuer Object ID for the common name type:OID value:2 5 4 3	2.5.4.3
value	Value of common name type:PrintableString value: SecureSign RootCA11	SecureSign RootCA11
ThisUpdate		value
ThisUpdate	the issue date of this CRL type:UTCTime value:yymmddhhmmssZ	
NextUpdate		value
NextUpdate	the date by which the next CRL will be issued type:UTCTime value:yymmddhhmmssZ	(12 month)

(Expansion Area)

authorityKeyIdentifier (extnId := 2 5 29 35, critical := FALSE)		value
AuthorityKeyIdentifier keyIdentifier	Certification Authority Key Identifier the identifier for the public key of CA which issued CRL type:OctetString value: hash of the value of the BIT STRING CA-PublicKey	5b f8 4d 4f b2 a5 86 d4 3a d2 f1 63 9a a0 be 09 f6 57 b7 de
cRLNumber (extnId := 2 5 29 20, critical := FALSE)		value
cRLNumber	serial number of CRL type:INTEGER value: unique positive integer	

(Entry Area)

RevokedCertificates		value
CertificateSerialNumber	serial number of revoked certificate type:INTEGER value: unique positive integer	
revocationDate	The date on which the revocation occurred type:UTCTime value:yymmddhhmmssZ	

(Entry Expansion Area)

invalidityDate (extnId ::= 2 5 29 24, critical ::= FALSE)		value
invalidityDate	the date on which it is known or suspected that the certificate became invalid type:GeneralizedTime value:yyymmddhhmmssZ	
cRLReason (extnId ::= 2 5 29 21, critical ::= FALSE)		value
cRLReason	the reason for the certificate revocation type: Enumerated value: reason code for the revocation	

OCSP Server Certificate

(Standard Area)

Version		value
Version	Version of the encoded certificate type:INTEGER value:2	2 (Ver.3)
SerialNumber		value
CertificateSerialNumber	Serial number of certificate type:INTEGER value: unique positive integer	*serial number 41 (0x29)
Signature		value
AlgorithmIdentifier	The identifier for the crypto-graphic algorithm used by the CA to sign this certificate (public key cryptosystem and hash) Object ID for the cryptographic algorithm (SHA-2) type:OID type:1 2 840 113549 1 1 11 Parameters of cryptographic algorithm type:NULL value:	sha256WithRSAEncryption NULL
Issuer		value
CountryName type	Country-name attribute of the certificate issuer Object ID for the country name type:OID value:2 5 4 6	2.5.4.6
value	Value of country name type:PrintableString value:JP	JP
OrganizationName type	Organization-name attribute of the certificate issuer Object ID for the country name type:OID value:2 5 4 10	2.5.4.10
value	Value of organization name type:PrintableString value: Japan Certification Services, Inc.	Japan Certification Services, Inc.
CommonName type	Common-name attribute of the certificate issuer Object ID for the common name type:OID value:2 5 4 3	2.5.4.3
value	Value of common name type:PrintableString value: SecureSign RootCA11	SecureSign RootCA11
Validity		value
Validity notBefore	Validity period of certificate the date on which the certificate validity period begins type:UTCTime value:160306064915Z	*the date on which the certificate validity period begins March 6, 2017, 06:49:15(GMT)
notAfter	The date on which the certificate validity period ends type:UTCTime value:190331145959Z	*the date on which the certificate validity period ends March 31, 2019, 14:59:59(GMT)
Subject		value
CountryName type	Country-name attribute of the certificate issuer Object ID for the country name type:OID value:2 5 4 6	2.5.4.6
value	Value of country name type:PrintableString value:JP	JP
OrganizationName type	Organization-name attribute of certificate issuer Object ID for the organization name type:OID value:2 5 4 10	2.5.4.10
value	Value of organization name	

CommonName	type:PrintableString value: Japan Certification Services, Inc. Common-name attribute of the certificate issuer	Japan Certification Services, Inc.
type	Object ID for the common name type:OID value:2 5 4 3	2.5.4.3
value	Value of common name type:PrintableString value:SecureSign RootCA11 OCSP Responder	SecureSign RootCA11 OCSP Responder
subjectPublicKeyInfo		value
SubjectPublicKeyInfo	Subject's public key information	
AlgorithmIdentifier	The identifier for the cryptographic algorithm(public key cryptosystem and hash) Object ID for the cryptographic algorithm (RSA PUBLIC KEY) type:OID value:1 2 840 113549 1 1 1	1.2.840.113549.1.1.1
algorithm	Parameters of cryptographic algorithm type:NULL value:	NULL
parameters	Value of public key type: BIT STRING value: public key	public key of 2048 bit length
subjectPublicKey		

(Expansion Area)

basicConstraints (extnId ::= 2 5 29 19, critical ::= FALSE)		value
BasicConstraints cA	Basic Constraints The flag to determine whether the supplied certificate is associated with a CA type:Boolean value: FALSE(not associated with the CA)	FALSE
authorityKeyIdentifier (extnId ::= 2 5 29 35, critical ::= FALSE)		value
authorityKeyIdentifier keyIdentifier	Certification Authority Key Identifier The identifier for the public key type:OctetString value: Hash of the value of certificate issuer's PublicKey	5b f8 4d 4f b2 a5 86 d4 3a d2 f1 63 9a a0 be 09 f6 57 b7 de
subjectKeyIdentifier (extnId ::= 2 5 29 14, critical ::= FALSE)		value
SubjectKeyIdentifier keyIdentifier	Subject Key Identifier The identifier for the public key type:OctetString value: Hash of the value of the subject's PublicKey	B9:49:42:CC:DD:D7:42:9F:7D:A1: 8F:E3:B6:08:F5:C9:BA:26:55:96
keyUsage (extnId ::= 2 5 29 15, critical ::= FALSE)		value
KeyUsage	The purpose of the key type:BitString value:100000000 (digitalSignature)	100000000
extKeyUsage (extnId ::= 2 5 29 31, critical ::= FALSE)		value
extendedKeyUsage	Purpose of the key usage (extension)	
KeyPurposeID OCSPSigning	ID for the purpose of the key usage type:OID value: Online responder signature usage	1.3.6.1.5.5.7.3.9
OCSP No Check (extnId ::= 1.3.6.1.5.5.7.48.1.5, critical ::= FALSE)		value
OCSP No Check OCSP No Check	Revocation checking of signer's certificates Do not check revocation	NULL

JCSI Subordinate CA Certificate (reference)

(Standard Area)

Version		value
Version	version of the encoded certificate type:INTEGER value:2	2 (Ver.3)
SerialNumber		value
CertificateSerialNumber	serial number of certificate type:INTEGER value: unique positive integer	*serial number(random serial number)
Signature		value
AlgorithmIdentifier	the identifier for the crypto-graphic algorithm used by the CA to sign this certificate	
Algorithm	(public key cryptosystem and hash) Object ID for the cryptographic algorithm (SHA-256) type:OID value:1 2 840 113549 1 1 11	1.2.840.113549.1.1.11
parameters	Parameters of cryptographic algorithm type:NULL value:	NULL
Issuer		value
CountryName	Country-name attribute of certificate issuer	
type	Object ID for the country name type:OID value:2 5 4 6	2.5.4.6
value	Value of country name type:PrintableString value:JP	JP
OrganizationName	Organization-name attribute of certificate issuer	
type	Object ID for the organization name Type: OID Value: 2 5 4 10	2.5.4.10
value	Value of organization name Type: PrintableString Value: Japan Certification Services, Inc.	Japan Certification Services, Inc.
CommonName	Common-name attribute of certificate issuer	
Type	Object ID for the common name type:OID value:2 5 4 3	2.5.4.3
value	Value of common name type:PrintableString Value: SecureSign RootCA11	SecureSign RootCA11
Validity		value
Validity	Validity period of certificate	
notBefore	the date on which the certificate validity period begins type:UTCTime value:yymmddhhmmssZ	*the certificate validity period begins yymmddhhmmssZ (issuance date, time)
notAfter	the date on which the certificate validity period ends type:UTCTime Value:yymmddhhmmssZ	*the certificate validity period ends 290408045647Z (April 8, 2029 4:56:47 GMT)
Subject		value
CountryName	Country-name attribute of certificate subject	
type	Object ID for the country name type:OID value:2 5 4 6	2.5.4.6
value	Value of country name type:PrintableString value:JP	JP
OrganizationName	Organization-name attribute of certificate subject	
type	Object ID for the organization name type:OID value:2 5 4 10	2.5.4.10
value	Value of organization name	

CommonName	type:PrintableString value: Cybertrust Japan Co., Ltd. Common-name attribute of certificate subject	Cybertrust Japan Co.,Ltd.
type	Object ID for the common name	
value	type:OID value:2 5 4 3 Value of common name type:PrintableString value:JCSI TLSSign Public CA	2.5.4.3 JCSI TLSSign Public CA (example)
subjectPublicKeyInfo		value
SubjectPublicKeyInfo	Subject's public key information	
AlgorithmIdentifier	the identifier for the cryptographic algorithm(public key cryptosystem and hash)	
algorithm	Object ID for the cryptographic algorithm (RSA PUBLIC KEY) type:OID value:1 2 840 113549 1 1 1	1.2.840.113549.1.1.1
parameters	Parameters of cryptographic algorithm type:NULL value:	NULL
subjectPublicKey	Value of public key type: BIT STRING value: public key	public key of 2048 bit length

(Expansion Area)

certificatePolicies (extnId ::= 2 5 29 32, critical ::= FALSE)		value
PolicyInformation	Information of the Policy	
policyIdentifier	type:OID value:2.5.29.32.0 (anyPolicy)	2.5.29.32.0
policyQualifiers	Information of the policy qualifiers	
policyQualifierID	Classification of policy qualifiers type:OID value: Object ID of CPS URI (id-qt-cps)	1.3.6.1.5.5.7.2.1
Qualifier	URI of CPS is published type:OctetString value:https://www.cybertrust.ne.jp/jcsi/repository.html	https://www.cybertrust.ne.jp/jcsi/repository.html
authorityInfoAccess (extnId ::= 1 3 6 1 5 5 7 1 1, critical ::= FALSE)		value
Authority Information Access	Authority Information Access	
Ocsp	Online Certificate Status Protocol type:OID value:1.3.6.1.5.5.7.48.1 type:OctetString value: http://rtocsp.managedpki.ne.jp/OcspServer	1.3.6.1.5.5.7.48.1 http://rtocsp.managedpki.ne.jp/OcspServer
Caissuers	Access method type:OID value:1.3.6.1.5.5.7.48.2 type:OctetString value: http://rtocsp.managedpki.ne.jp/SecureSignAD/SecureSignRootCA11/SSAD-rca.crt	1.3.6.1.5.5.7.48.2 http://rtocsp.managedpki.ne.jp/SecureSignAD/SecureSignRootCA11/SSAD-rca.crt
extendedKeyUsage (extnId ::= 2 5 29 37, critical ::= FALSE)		value
extendedKeyUsage	key usage (extension)	
KeyPurposeID	Key Purpose ID	
serverAuth	Type:OID Value: serverAuth	1.3.6.1.5.5.7.3.1
authorityKeyIdentifier (extnId ::= 2 5 29 35, critical ::= FALSE)		value
AuthorityKeyIdentifier	Certificate Authority Key Identifier	
keyIdentifier	the identifier for the public key of CA which issued CRL type:OctetString value: hash of the value of the BIT STRING CA-PublicKey	5b:f8:4d:4f:b2:a5:86:d4:3a:d2:f1:63:9a:a0:be:09:f6:57:b7:de
cRLDistributionPoints (extnId ::= 2 5 29 31, critical ::= FALSE)		value
cRLDistributionPoints	CRL Distribution Point	
DistributionPoint	CRL Distribution Point	
uniformResourceIdentifie	URI	

	type:OctetString value: http://rtctrl.managedpki.ne.jp/SecureSign AD/SecureSignRootCA11/cdp.crl	http://rtctrl.managedpki.ne.jp/SecureSign AD/SecureSignRootCA11/cdp.crl
subjectKeyIdentifier (extnId ::= 2 5 29 14, critical ::= FALSE)		value
SubjectKeyIdentifier keyIdentifier	Subject Key Identifier the identifier for the public key type:OctetString value: hash of the value of the BIT STRING subjectPublicKey	(hash value of subjectPublicKey)
basicConstraints (extnId ::= 2 5 29 19, critical ::= TRUE)		value
BasicConstraints cA	Basic Constraints The flag to determine whether the supplied certificate is associated with a CA or an end entity type:Boolean value: True (associated with the CA)	TRUE
PathLenConstraint	PathLenConstraint type:INTEGER value:0 (do not have subordinate CA)	0
Name Constraints (extnId ::= 2.5.29.30, critical ::= TRUE)		value
Name Constraints Permitted Names	Name Constraints dNS Name Directory Name	.managedpki.ne.jp O=Cybertrust Japan Co.,Ltd., L=Minato-ku, ST=Tokyo, C=JP
Excluded Names	IP address (IPv4) IP address (IPv6)	0.0.0.0/0.0.0.0 0:0:0:0:0:0:0:0/0
keyUsage (extnId ::= 2 5 29 15, critical ::= TRUE)		value
KeyUsage	the purpose of the key contained in the certificate type:BitString value:10000110 (Digital Signature,keyCertSign,cRLSign)	10000110 (0x86)

JCSI SSL/TLS Certificate (reference)

(Standard Area)

Version		value
Version	version of the encoded certificate type:INTEGER value:2	2 (Ver.3)
Serialnumber		value
CertificateSerialNumber	serial number of certificate type:INTEGER value: unique positive integer	*serial number(random serial number)
Signature		value
AlgorithmIdentifier	the identifier for the crypto-graphic algorithm used by the CA to sign this certificate (public key cryptosystem and hash) Object ID for the cryptographic algorithm (SHA-256) type:OID value:1 2 840 113549 1 1 11	1.2.840.113549.1.1.11
Parameters	Parameters of cryptographic algorithm type:NULL value:	NULL
Issuer		value
CountryName	Country-name attribute of certificate issuer Object ID for the country name type:OID value:2.5.4.6	2.5.4.6
Type		
Value	Value of country name type:PrintableString value:JP	JP
OrganizationName	Organization-name attribute of certificate issuer Object ID for the organization name type:OID value:2.5.4.10	2.5.4.10
Type		
Value	Value of organization name type:PrintableString value: Cybertrust Japan Co., Ltd.	Cybertrust Japan Co.,Ltd.
CommonName	Common-name attribute of certificate issuer Object ID for the common name type:OID value:2.5.4.3	2.5.4.3
Type		
Value	Value of common name type:PrintableString value:JCSI TLSSign Public CA	JCSI TLSSign Public CA
Validity		value
Validity	Validity period of certificate	* the validity period: 25 months, editable
notBefore	the date on which the certificate validity period begins type:UTCTime value:yymmddhhmmssZ	* the date and time on which the certificate validity period begins
notAfter	the date on which the certificate validity period ends type:UTCTime value:yymmddhhmmssZ	* the date and time on which the certificate validity period ends
Subject		value
CountryName	Country-name attribute of certificate subject Object ID for the country name type:OID value:2.5.4.6	2.5.4.6
Type		
value	Value of country name type:PrintableString value: country name attribute of certificate subject	JP
StateOrProvinceName	State or Province -name attribute of certificate subject Object ID for the state or province name	
type		

value	type:OID value:2.5.4.8	2.5.4.8
LocalityName	value of state or province name type:PrintableString / UTF8String value: state or province name attribute of certificate subject	Tokyo
type	Locality-name attribute of certificate subject	
value	Object ID for the locality name type:OID value:2.5.4.7	2.5.4.7
OrganizationName	Value of locality name type:PrintableString / UTF8String value: locality name attribute of certificate subject	Minato-ku
type	Organization-name attribute of certificate issuer	
value	Object ID for the organization name type:OID value:2.5.4.10	2.5.4.10
CommonName	Value of organization name type:PrintableString / UTF8String value: organization name attribute of certificate issuer	Cybertrust Japan Co.,Ltd.
type	Common-name attribute of certificate issuer	
value	Object ID for the common name type:OID value:2.5.4.3	2.5.4.3
	Value of common name type:PrintableString value: common name attribute of certificate issuer	* FQDN of the SSL/TLS server * Note: domain: .managedpki.ne.jp
subjectPublicKeyInfo		value
SubjectPublicKeyInfo	Subject's public key information	
AlgorithmIdentifier	the identifier for the cryptographic algorithm(public key cryptosystem and hash)	
algorithm	Object ID for the cryptographic algorithm (RSA PUBLIC KEY) type:OID value:1.2.840.113549.1.1.1	1.2.840.113549.1.1.1
parameters	Parameters of cryptographic algorithm type:NULL value:	NULL
subjectPublicKey	Value of public key type: BIT STRING value: Value of public key	* the key length is depended on application * the key length must be at least 2048-bit

(Expansion Area)

basicConstraints (extnId ::= 2.5.29.19, critical ::= TRUE)		value
BasicConstraints	Basic Constraints	
cA	The flag to determine whether the supplied certificate is associated with a CA or an end entity type:Boolean value: FALSE(not associated with the CA)	FALSE
certificatePolicies (extnId ::= 2.5.29.32, critical ::= FALSE)		value
PolicyInformation	Information of the Policy	
policyIdentifier	type:OID value:1.2.392.00200081.1.10.10	1.2.392.00200081.1.10.10
policyQualifiers	Information of the policy qualifiers	
policyQualifierID	Classification of policy qualifiers type:OID value: Object ID of CPS URI (id-qt-cps)	1.3.6.1.5.5.7.2.1
Qualifier	URI of CPS is published type: URL value: https://www.cybertrust.ne.jp/jcsi	https://www.cybertrust.ne.jp/jcsi/reposito

policyIdentifier	/repository.html type:OID value:2.23.140.1.2.2	ry.html 2.23.140.1.2.2
subjectAltName (extnId ::= 2.5.29.17, critical ::= FALSE)		value
dnsName	dnsName type:IA5String value: common name attribute of certificate issuer	* FQDN of the SSL/TLS server * Note: Domain: .managedpki.ne.jp
authorityInfoAccess (extnId ::= 1.3.6.1.5.5.7.1.1, critical ::= FALSE)		value
Authority Information Access Ocsp	Authority Information Access Online Certificate Status Protocol type:OID value:1.3.6.1.5.5.7.48.1 type:OctetString value: http://jcsitlssignpublicca-ocsp.managedpki.ne.jp/OcspServer	1.3.6.1.5.5.7.48.1 http://jcsitlssignpublicca-ocsp.managedpki.ne.jp/OcspServer
Caissuers	Access Method type:OID value:1.3.6.1.5.5.7.48.2 type:OctetString value: http://rtctrl.managedpki.ne.jp/SecureSignAD/JCSITLSSignPublicCA/SSAD-JCSITLS.crt	1.3.6.1.5.5.7.48.2 http://rtctrl.managedpki.ne.jp/SecureSignAD/JCSITLSSignPublicCA/SSAD-JCSITLS.crt
keyUsage (extnId ::= 2.5.29.15, critical ::= TRUE)		value
KeyUsage	the purpose of the key contained in the certificate type:BitString value:1010000 (digitalSignature,keyEncipherment)	1010000(0xa0)
extendedKeyUsage (extnId ::= 2.5.29.37, critical ::= FALSE)		value
extendedKeyUsage	in addition to or in place of the basic purposes indicated in the key usage extension field	
KeyPurposeID serverAuth	Key Purpose ID type:OID value:1.3.6.1.5.5.7.3.1	1.3.6.1.5.5.7.3.1(serverAuth)
clientAuth	type:OID value:1.3.6.1.5.5.7.3.2	1.3.6.1.5.5.7.3.2(clientAuth)
authorityKeyIdentifier (extnId ::= 2.5.29.35, critical ::= FALSE)		value
AuthorityKeyIdentifier keyIdentifier	Certificate Authority Key Identifier the identifier for the public key type:OctetString value: hash of the value of the BIT STRING subjectPublicKey	* hash value of the PublicKey of SubCA
cRLDistributionPoints (extnId ::= 2.5.29.31, critical ::= FALSE)		value
cRLDistributionPoints DistributionPoint uniformResourceIdentifie	CRL Distribution Point CRL Distribution Point URI type:OctetString value: http://rtctrl.managedpki.ne.jp/SecureSignAD/JCSITLSSignPublicCA/cdp.crl	http://rtctrl.managedpki.ne.jp/SecureSignAD/JCSITLSSignPublicCA/cdp.crl
subjectKeyIdentifier (extnId ::= 2.5.29.14, critical ::= FALSE)		value
SubjectKeyIdentifier keyIdentifier	Subject Key Identifier the identifier for the public key type:OctetString value: hash of the value of the BIT STRING subjectPublicKey	* hash value of subjectPublicKey